烧料触线 GreenTouch

2704A 27.0" Android Touch All-in-One Is Stylish

Greentouch's 2704A 27.0" Touch All-in-One is stylish, flexible, and functional for POS, retail and hospitality applications, and is the most versatile and powerful Android system available today, Using ARM R18, 4 nuclear A7 1.2G processor.For higher performance or greater storage capacity requirements for customers, ARM R18, 8 nuclear A7 1.8G to increase the 2GB RAM option kit or 16GB hard drive is the option and the performance can be increased significantly.

The 2704A is available with a choice of industry-leading GreenTouch touch technologies: 10 touch projected capacitive(PCAP). Worldwide agency approvals cover the whole model, which is developed, built, serviced and supported by a true singlesource supplier. The 2704A All-in-One is stylish provides an economical solution for system integrators and VARs.

Benefits:

 Choice of GreenTouch optional touch technologies:
10 touch projected capacitive (PCAP);

•Compact and easy to integrate with mounting from sides or top and bottom; also a VESA mount option

- · Worldwide agency approvals
- One year standard warranty

• "Designed for touch" from the ground up

· Reliability, quality and cost-effective

About GreenTouch

Shenzhen GreenTouch Technology Co., Ltd. is a professional manufacturer of touch screen and a high-tech enterprise. Our company specializes in R&D, manufacture and marketing of high-grade touch screen and value-added touch screen. Our company has our own trademark--Green-Touch and provides customers with touch screens including SAW touch screen, IR touch screen, four-wire touch screen, five-wire touch screen and various touch screen monitors. GreenTouch has automatic production lines and the sealed dust-free workshops and has been certified to ISO9001 Quality Management System and ISO14001 Environmental Management System. The products are inspected in strict accordance with the quality management system. Quality management becomes an essential part of operation. Our products have been certified to CE, FCC, ETL, ROHS and UL. The objective of GreenTouch is to become the most reliable supplier of touch screen, special products, high value-added products and touch solutions in the world!

Specifications

Case/Bezel color	Plastic Black;White(option)				
Display type	27" diagonal, 16:9, Active matrix TFTLCD				
Optimal (native)					
resolution	1920 x 1080 @ 60Hz				
	Width: 23.44" (595.5 mm)				
Monitor dimensions	Height : 13.24" (363.1 mm)				
	Depth: 1.62' (43.03mm)				
Useful screen area	Horizont al: 23.53" (597.6 mm); Vertical: 13.23" (336.15 mm)				
Colors	16.7M				
Brightness (typical)	LCD panel:300 nits;				
Response time	5 msec				
View ing angle (from	Horizontal (left / right): 170° total; Vertical (up:80°				
center)	/dow n:80°):160° total				
Contrast ratio	1000:1(typical)				
Touch technology	PCAP				
ARM	Allw inner R18, A7, 64Bit, 4 cores 1.2G,				
	Allw inner A83, A7, 64Bit, 8 cores 1.8G (option)				
RAM	1GB,2GB(option)				
FLASH	8G, (option)16G,32G				
U SB port	2 xU SB2.0				
OTG	Micro usb				
SD CARD	1x card				
Ethemet	1 x LAN RJ45				
wireless	internal (802.11b/g/n)				
Bluetooth	BT4.0				
Earphone port	1 x 3.5mm Earphone port				
Speaker	2X speaker inside				
	Input power connector specification (on monitor)—Type: DC				
	Barrel Jack; Barrel inner				
Powersupply	diameter: 4.2 mm (±0.3 mm); Pin outer diameter: 1.7 mm (+0.0 -				
	0.1 mm); Barrel dept h:				
	8.8mm (±0.3mm)				
Pow er consumption	28W (†ypical)				
Operating system	Android				
Video planer	Support 1080P H265				
Temperature	Operating: $0^{\circ}C \sim 35^{\circ}C(32^{\circ}F - 95^{\circ}F)$; Storage: $-20^{\circ}C \sim 60^{\circ}C$				
	(-4°F - 140°F)				
Humidity	Operating: 20%~80%; Storage: 5%~95%				
W eight (approx.)	Actual:15lbs (7kg); Shipping: 26.5lbs (12kg) (reference)				
M ounting options	100mm /75*70 VESA mount				
Agency Certification	U L,cU L (Recognized), FCC, CE,, China RoHS				

Applications:

- Kiosk information systems
- Gaming and amusement
- Industrial automation
- Self-service Kiosk





Ordering Information

		1		1		Surface	1
Model	Part Number	Technology	ARM	RAM	Flash		Availability
						Treatment	
2704A	GT-TC-2704A-CTAR-R18-1R8G	PCAP	R18 4 cores 1.2G	1G	8G	Clear	W orldw ide
2704A	GT-TC-2704A-CTAR-R18-2R8G	PCAP	R184 cores 1.2G	2G	8G	Clear	W orldw ide
2704A	GT-TC-2704A-CTAR-R18-2R16G	PCAP	R184 cores 1.2G	2G	16G	Clear	W orldw ide
2704A	GT-TC-2704A-CTAR-R18-2R32G	PCAP	R184 cores 1.2G	2G	32G	Clear	W orldw ide
2704A	GT-TC-2704A-CTAR-A83-1R8G	PCAP	A838 cores 1.8G	1G	8G	Clear	W orldw ide
2704A	GT-TC-2704A-CTAR-A83-2R8G	PCAP	A838 cores 1.8G	2G	8G	Clear	W orldw ide
2704A	GT-TC-2704A-CTAR-A83-2R16G	PCAP	A838 cores 1.8G	2G	16G	Clear	W orldw ide
2704A	GT-TC-2704A-CTAR-A83-2R32G	PCAP	A838 cores 1.8G	2G	32G	Clear	W orldw ide

To find out more about our extensive range of GreenTouch touch solutions, go to www.greentouch.com.cn, or ifo@greentouch.com.cn Service call:+86-755-29370883/29371519

Shenzhen GreenTouch Technology Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. GreenTouch (logo) and Shenzhen GreenTouch Technology Co., Ltd. Copyright . All rights reserved. 2016 Shenzhen GreenTouch Technology Co., Ltd. All rights reserved.