

Shenzhen Tongdazhi Technology Co., Ltd

TDZ-S311

Tripod Turnstile



Feature

- ❖ Running stable without noise and mechanical impact
- ❖ Equipped with the dry contact signal input interface, compatible with all kinds of access controllers.
- ❖ After swiping card in normal condition, if within the permitting time passages do not pass, the system will cancel the users' pass right and arm close automatically
- ❖ Arm automatically open when the power off to make sure safety In case of emergency
- ❖ Optional for external counter to record the people numbers for each lane
- ❖ Single way or Bi-directional adjustable based on the requirement
- ❖ Equipped with LED directional indication / status lights

Occasion Application

Suitable for commercial buildings, subways, airports, customs, exhibition halls, government buildings, financial institutions, clubs and other high-end indoor applications.

Parameters

Structure parameters

Housing material	304 grade stainless steel
Thickness	1.5mm + 1.0mm
Surface treatment	Brushed finish
Technical parameters	
Size	420*330*980mm
Lane width	600mm
Passing speed	35--50 people/min
Open/close speed	0.2sec
Weight	60KG
Turning angle	120 degree
MCBF	5.000.000 times
Application	Indoor or outdoor
Rotating directional	Single way or Bi-directional adjustable
Noise	<55db
Operating temperature	-15 to 70℃
Relative humidity	5% to 95%
Package	Carton box inside. Wooden case outside
Electronic parameters	
Power supply	110-220V/AC, 50/60HZ
Rated power	100W
Input signal	Dry contact
Driving motor	Solenoid
Method of position	Limiter

Basic Function

- ✧ The entry and exit directional can be set independently, free mode / forbidden model
- ✧ Direction indicator: The direction indicator is installed on the top of the housing cabinet to indicate the valid passing direction
- ✧ Compatibility: Equipped with dry contact signal input interface can make sure compatible with all kinds of access controllers
- ✧ Arm will drop down automatically when the power off. Which is meets the firefighting requirement

Customized Function

- Built-in or external counter
- External gate open button or remote controller
- 316 grade stainless steel. Thickness of the material
- Integrate with access control system and built-in reader appointed by customers.