

DKM36PCS

165W/160W/155W/150W

PRODUCT SPECIFICATION

DKM36PCS 165W/160W/155W/150W

PRODUCT SPECIFICATION

Electrical parameters at standard test conditions
(STC:AM=1.5, 1000W/m², Cells Temperature 25°C)

Typical type	165W	160W	155W	150W
Max power(Pmax)	165	160	155	150
Max power voltage(Vmp)	18.92	18.89	18.66	18.61
Max power current(Imp)	8.72	8.47	8.3	8.06
Open circuit voltage(Voc)	22.71	22.67	22.39	22.33
Short circuit current(Isc)	9.85	9.57	9.37	9.1
Cell efficiency(%)	19.75	19.16	18.56	17.96
Module Efficiency(%)	16.37	15.87	15.38	14.88
Max system voltage	DC1000V			
Maximum Series Fuse Rating	15A			

Mechanical Data

Dimensions	1480*680*30/35mm
Weight	12kgs
Front glass	3.2 mm tempered glass
Output cables	4 mm ² symmetrical lengths 900 mm
Connectors	MC4 compatible IP67
Cell type	Mono Crystalline Silicon 156mmx156mm
Number of cells	36 cells in series

Temperat Ure Characteristics

Temp.Coeff.of Isc(TK Isc)	0.037% / °C
Temp.Coeff.of Voc(TK Voc)	(-0.34%) / °C
Temp.Coeff.of Pmax(TK Pmax)	(-0.48%) / °C
Operating temperature	(-40~+85%) °C
Normal operating cell temperature	45±2°C

Packing Configuration

Container	20'GP	40'GP	40'HQ
Pieces per pallet	64	64	80
Pallets per container	7	15	15
	448	960	1200

Tests,Certificati Ons and Warranties

Standard tests	IEC 61215, IEC 61730
System certs	ISO 9001, ISO14001
Certifications	TUV,CE,MCS,PV CYCLE,CEC,CHUBB
Extreme wind and snow loads testing	Withstand extreme wind(2400 Pascal) and snow loads(5400 Pascal)
Positive tolerance	0~ +3%
Junction box	≥ IP65
Warranties	10 years material and workmanship and 25 years output at least 80%

DKP36PCS

140W/145W/150W/155W

PRODUCT SPECIFICATION

DKP36PCS 140W/145W/150W/155W

PRODUCT SPECIFICATION

Electrical parameters at standard test conditions
(STC:AM=1.5, 1000W/m², Cells Temperature 25°C)

Typical type	155W	150W	145W	140W
Max power(Pmax)	155	150	145	140
Max power voltage(Vmp)	18.42	18.23	17.8	17.6
Max power current(Imp)	8.41	8.22	8.15	7.95
Open circuit voltage(Voc)	22.1	21.87	21.96	21.96
Short circuit current(Isc)	9.5	9.28	8.5	8.41
Cell efficiency(%)	18.22	17.64	17.05	16.46
Module Efficiency(%)	15.38	14.88	14.39	13.89
Max system voltage	DC1000V			
Maximum Series Fuse Rating	15A			

Mechanical Data

Dimensions	1480*680*30/35mm
Weight	12kgs
Front glass	3.2 mm tempered glass
Output cables	4 mm ² symmetrical lengths 900 mm
Connectors	MC4 compatible IP67
Cell type	Poly Crystalline Silicon 156mmx156mm
Number of cells	36 cells in series

Temperat Ure Characteristics

Temp.Coeff.of Isc(TK Isc)	0.045% / °C
Temp.Coeff.of Voc(TK Voc)	(-0.34%) / °C
Temp.Coeff.of Pmax(TK Pmax)	(-0.47%) / °C
Operating temperature	(-40~+85%) °C
Normal operating cell temperature	45±2°C

Packing Configuration

Container	20'GP	40'GP	40'HQ
Pieces per pallet	64	64	80
Pallets per container	7	15	15
	448	960	1200

Tests,Certificati Ons and Warranties

Standard tests	IEC 61215, IEC 61730
System certs	ISO 9001, ISO14001
Certifications	TUV,CE,MCS,PV CYCLE,CEC,CHUBB
Extreme wind and snow loads testing	Withstand extreme wind(2400 Pascal) and snow loads(5400 Pascal)
Positive tolerance	0~ +3%
Junction box	≥ IP65
Warranties	10 years material and workmanship and 25 years output at least 80%

