



FPC INTERFACE

NO.	SYMBOL
1	LED-K1
2	LED-K2
3	LED-A1
4	LED-A2
5	NC
6	RESET
7	NC
8	YU(NC)
9	XR(NC)
10	YD(NC)
11	XL(NC)
12	B0
13	B1
14	B2
15	B3
16	B4
17	B5
18	B6
19	B7
20	G0
21	G1
22	G2
23	G3
24	G4
25	G5
26	G6
27	G7
28	R0
29	R1
30	R2
31	R3
32	R4
33	R5
34	R6
35	R7
36	HSYNC
37	VSYNC
38	DCLK
39	VCI
40	VCI
41	VCC
42	VCC
43	CS
44	NC
45	NC
46	NC
47	NC
48	NC
49	SCL
50	SDI
51	NC
52	ENABLE
53	GND
54	GND

NOTES:

- 1. DISPLAY TYPE: 3.5" TFT
- 2. VIEWING DIRECTION: 6 O'CLOCK.
- 3. POLARIZER MODE: TRANSMISSIVE/NEGATIVE.
- 4. OPERATING TEMP: -20°C ~ +70°C.
- 5. STORAGE TEMP: -30°C ~ +80°C.
- 6. BACKLIGHT: 7-WHITE LED
- 7. CONNECTOR: COG/HX8238D



Electrical Circuit:
LED: 1*6=6 PCS

RX Reshine Display (HK) Technology Co., Limited

LCM NO: RXL035038-A	FPC NO. A:	VERSION: 1.0
	FPC NO. B:	NO.: 1 OF 1
DESIGNED BY: QSC	FPC NO. C:	UNIT: MM
		DATE: 2010.04.08