



1	LED_Cathode	31	R3
2	LED_Cathode	32	R4
3	LED_Anode	33	R5
4	LED_Anode	34	R6
5	NC	35	R7
6	RESTET	36	HSYNC
7	NC	37	VSYNC
8	YU	38	DOTCLK
9	XR	39	NC
10	YD	40	NC
11	XL	41	VDD
12	B0	42	VDD
13	B1	43	/CS
14	B2	44	NC
15	B3	45	NC
16	B4	46	NC
17	B5	47	NC
18	B6	48	NC
19	B7	49	SCK
20	G0	50	SDI
21	G1	51	NC
22	G2	52	ENB
23	G3	53	GND
24	G4	54	GND
25	G5		
26	G6		
27	G7		
28	R0		
29	R1		
30	R2		



背光电路图 (CIRCUIT DIAGRAM)
If=20mA, V=19.2 (TYP.)

Specification:

- 1). Luminance: **300nits**
- 2). Display mode: a_Si TFT/Transmissive/Normal White
- 3). Operating temp.: -20°C~+70°C
Storage temp.: -30°C~+80°C
- 4). IC: HX8238-D
- 5). All the raw material are Rohs compliant

SCALE: FIT		
SHEET: 1 OF 1		
GENERAL TOL: ±0.2MM		
APP:	DATE:	MODEL NO: RXL035039-A
CHK:	DATE:	PART NO: RXL035039-A
DWN:	DATE:	TITLE: LCM