



www.kontakledlight.com



◆ 投射灯系列

PROJECTION LAMP SERIES

适用于大面积场矿、建筑物轮廓、体育场、立交桥、纪念碑、公园和花坛等户外照明场所。



技术参数

TECHNICAL PARAMETERS

产品型号 Item No	功率 Power	尺寸 Size	输入电压 Input voltage	色温 Color temperature	功率因数 Power factor	显指 RA	防护等级 IP
KTFL2032-F1	50W	310.5×220×50mm	AC85-265V	2600-6500K	>0.95	≥ 80	IP65
KTFL2032-F2	80W	354.5×245×55mm	AC85-265V	2600-6500K	>0.95	≥ 80	IP65
KTFL2032-F3	100W	402.5×295×60mm	AC85-265V	2600-6500K	>0.95	≥ 80	IP65
KTFL2032-F4	150W	430.5×330×60mm	AC85-265V	2600-6500K	>0.95	≥ 80	IP65
KTFL2032-F5	200W	470.5×360×60mm	AC85-265V	2600-6500K	>0.95	≥ 80	IP65

◆ 投射灯系列

PROJECTION LAMP SERIES

适用于大面积场矿、建筑物轮廓、体育场、立交桥、纪念碑、公园和花坛等户外照明场所。



技术参数

TECHNICAL PARAMETERS

产品型号 Item No	功率 Power	尺寸 Size	输入电压 Input voltage	色温 Color temperature	功率因数 Power factor	显指 RA	防护等级 IP
KTFL2031-G1	50W	310.5×220×50mm	AC85-265V	2600-6500K	>0.95	≥ 80	IP65
KTFL2031-G2	80W	354.5×245×55mm	AC85-265V	2600-6500K	>0.95	≥ 80	IP65
KTFL2031-G3	100W	402.5×295×60mm	AC85-265V	2600-6500K	>0.95	≥ 80	IP65
KTFL2031-G4	150W	430.5×330×60mm	AC85-265V	2600-6500K	>0.95	≥ 80	IP65
KTFL2031-G5	200W	470.5×360×60mm	AC85-265V	2600-6500K	>0.95	≥ 80	IP65
KTFL2031-G6	300W	565×457×65mm	AC85-265V	2600-6500K	>0.95	≥ 80	IP65