





Code	Name	picture	Device ratio/ wavelength	Spec			
KTGL0803	60*10w	 600W	Full spectrum	Parameter	Value	Parameter	Value
				dimension	200*165*60mm	Actual Power	73~81w
				Input voltage	86~264vAC	Output voltage	DC70~100vDC
				Color	Red/Blue/UV/IR/White	Lifespan	50000 hours
				Lumen		lux	40200lux/0.2m; 15630lux/0.4m
				PAR	750umol/0.3m	Case Color	All white
				NW	3.05kg	Area	1.35m2/0.5m;
				Inbox dimension	287*192*86MM	Inbox GW	3.65kg
				Outbox dimension	405*305*295MM	Outbox GW	19.1kg/4pcs
KTGL0803	100*10w		Full spectrum	Parameter	Value	Parameter	Value
				dimension	310*210*60mm	Actual Power	104.4W~110w
				Input voltage	86~264vAC	Output voltage	DC70~100vDC
				Color	Red/Blue/UV/IR/White	Lifespan	50000 hours
				Lumen	6500LM	lux	20200lux/0.2m;6470lux/0.4m,2930lux/0.6m,
				PAR	318umol/0.6m	Case Color	All white
				NW	2.4kg	Area	1.13m2/0.2m; 1.53m2/0.4m,
				Inbox dimension	370*280*115mm	Inbox GW	3kg
				Outbox dimension	47.5*38*29	Outbox GW	13kg/4pcs
KTGL0803	150*10w	 1500W	Full spectrum	Parameter	Value	Parameter	Value
				dimension	402*214*60mm	Actual Power	149.4W~161w
				Input voltage	86~264vAC	Output voltage	DC70~100vDC
				Color	Red/Blue/UV/IR/White	Lifespan	50000 hours
				Lumen	6500LM	lux	20200lux/0.2m;6470lux/0.4m,2930lux/0.6m,
				PAR	318umol/0.6m	Case Color	All white
				NW	2.4kg	Area	1.13m2/0.2m; 1.53m2/0.4m,
				Inbox dimension	453x278x117MM	Inbox GW	4kg
				Outbox dimension	576*470*255MM	Outbox GW	16kg/4pcs
KTGL0803	200*10w	 2000W	Full spectrum	Parameter	Value	Parameter	Value
				dimension	300*300*60mm	Actual Power	205.2W~210w
				Input voltage	86~264vAC	Output voltage	DC70~100vDC
				Color	Red/Blue/UV/IR/White	Lifespan	50000 hours
				Lumen	6500LM	lux	20200lux/0.2m;6470lux/0.4m,2930lux/0.6m,
				PAR	318umol/0.6m	Case Color	All white
				NW	4kg	Area	1.13m2/0.2m; 1.53m2/0.4m,
				Inbox dimension	420*335*95MM	Inbox GW	4.5kg
				Outbox dimension	435*350*410MM	Outbox GW	18kg/4pcs