










Code	Name	Picture	Device ratio/ wavelength	Spec			
KTGL0809-ZNET2	36*3W		630nm:660nm:450nm:460nm:730nm:420nm=8:4:4:2:2:1:1	Parameter	Specification	Parameter	Specification
				dimension	L300*W100*H70mm	Actual Power	55~60w
				Input voltage	AC85~264V	Output voltage	DC75~95V
				Color	Red/Blue/UV/IR	Lifespan	50,000 hours
				Lumen	2000lm	lux	11200lux/0.5m 5280lux/1.0m
				PAR	260umol/60cm	Case color	Red
				NW	1.65kg	Area	0.75m2/0.5m; 1.3m2/1.0m
				Inbox dimension	38.3*18.3*12cm	Inbox GW	1.85kg
				Outbox dimension	38.3*18.3*12cm	Outbox GW	1.85kg/1pcs
				KTGL0809-ZNET 4	72*3W		630nm:660nm:450nm:460nm:730nm:420nm=8:4:2:2:1:1
dimension	L300*W300*H70mm	Actual Power	104W~110W				
Input voltage	AC85~264V	Output voltage	DC75~95V				
Color	Red/Blue/UV/IR	Lifespan	50,000 hours				
Lumen	4120lm	lux	19000lux/0.5m 9280lux/1.0m				
PAR	360umol/60cm	Case color	Red				
NW	3.35kg	Area	1.13m2/0.5m; 1.911m2/1.0m				
Inbox dimension	38.3*36.3*12cm	Inbox GW	4.35kg				
Outbox dimension	39.8*37.8*26.5cm	Outbox GW	18.6kg/4pcs				
KTGL0809-ZNET 6	108*3W		630nm:660nm:450nm:460nm:730nm:420nm=8:4:2:2:1:1				
				dimension	L450*W300*H80mm	Actual Power	156W~168W
				Input voltage	AC85~264V	Output voltage	DC75~95V
				Color	Red/Blue/UV/IR	Lifespan	50,000 hours
				Lumen	5940LM	lux	27500lux/0.5m 12500/1.0m
				PAR	490umol/60cm	Case color	Red
				NW	5.60KG	Area	1.57m2/0.5m;
				Inbox dimension	49*36.5*11cm	Inbox GW	6.03kg
				Outbox dimension	50.5*38*26.5cm	Outbox GW	13kg/2pcs
				KTGL0809-ZNET 8	144*3w		630nm:660nm:450nm:460nm:730nm:420nm=8:4:2:2:1:1
dimension	L600*W300*H80mm	Actual Power	206W~212W				
Input voltage	AC85~264V	Output voltage	DC32~45V				
Color	Red/Blue/UV/IR	Lifespan	50,000 hours				
Lumen	8000lm	lux	31200lux/0.5m 15500/1.0m				
PAR	530umol/60cm	Case color	Red				
NW	6.38kg	Area	2.05m2/0.5m;				
Inbox dimension	65.3*36.8*11cm	Inbox GW	7.45kg				
Outbox dimension	66.8*38*26.5cm	Outbox GW	16.3kg/2pcs				
KTGL0809-	162*3W		630nm:660nm:450nm:460nm:730nm				
				dimension	L450*W450*H70mm	Actual Power	266W~278W
				Input voltage	AC85~264V	Output voltage	DC75~95V
				Color	Red/Blue/UV/IR	Lifespan	50,000 hours
				Lumen	9150LM	lux	32300 Lux/0.5m 19300lux/1.0m

Znet 9	102*3W		m: 420nm=8:4:2:2:1:1	PAR	530umol/60cm	Case color	Red
				NW	7.37kg	Area	2.8M2/0.5m , 3.02m2/1.0m
				Inbox dimension	59.3x 57*12.3cm	Inbox GW	8.97kg
				Outbox dimension	60.8x 59.5x 27cm	Outbox GW	19.34kg/2pcs
KTGL0809-Znet 12	226*3W		630nm:660nm:450nm:460nm:730nm:420nm=8:4:2:2:1:1	Parameter dimension	Specification L663*W497*H80mm	Parameter Actual Power	Specification 356~386w
				Input voltage	AC85~264V	Output voltage	DC75~95V
				Color	Red/Blue/UV/IR	Lifespan	50,000 hours
				Lumen	11880LM	lux	38600lux/0.5 23300lux/1.0m
				PAR	657umol/60cm	Case color	Red
				NW	10.8kg	Area	3.15m2/0.5m; 3.57m2/1.0m
				Inbox dimension	76.3x 12.3x 57CM	Inbox GW	12kg
				Outbox dimension	763*570*123mm	Outbox GW	12kg/1pc
KTGL0809-Znet12-2	226*3W			Parameter dimension	Specification L902*W300*H80mm	Parameter Actual Power	Specification 356~386w
				Input voltage	AC85~264V	Output voltage	DC75~95V
				Color	Red/Blue/UV/IR	Lifespan	50,000 hours
				Lumen	11880LM	lux	32100lux/0.5m 20150lux/1.0m
				PAR	552umol/60cm	Case color	Red
				NW	9.64KG	Area	3.45m2/0.5m; 3.68m2/1.0m
				Inbox dimension	95.5*36.8*11cm	Inbox GW	11.44kg/pc
				Outbox dimension	95.5*36.8*11cm	Outbox GW	11.44kg/pc
KTGL0809-Znet16	288*3W		630nm:660nm:450nm:460nm:730nm:420nm=8:4:2:2:1:1	Parameter dimension	Specification L600*W600*H70mm	Parameter Actual Power	Specification 481~521w
				Input voltage	AC85~264V	Output voltage	DC75~95V
				Color	Red/Blue/UV/IR	Lifespan	50,000 hours
				Lumen	15840lm	lux	40700lux/0.5M 29000lux/1.0m
				PAR	720umol/0.3M	Case color	Red
				NW	13.68KG	Area	4.22m2/0.5m; 4.86m2/1.0m
				Inbox dimension	723*760*123mm	Inbox GW	15.68kg/pc
				Outbox dimension	723*760*123mm	Outbox GW	15.68kg/1pc
KTGL0809-Znet16-2	288*3W		630nm:660nm:450nm:460nm:730nm:420nm=8:4:2:2:1:1	Parameter dimension	Specification L1200*W300*H70mm	Parameter Actual Power	Specification 481~521w
				Input voltage	AC85~264V	Output voltage	DC75~95V
				Color	Red/Blue/UV/IR	Lifespan	50,000hours
				Lumen	15840lm	lux	37700lux/0.5M 25000lux/1.0m
				PAR	621umol/60cm		Red
				NW	13.68KG	Area	4.53m2/0.5m; 5.21m2/1.0m
				Inbox dimension	1253*368*123mm	Inbox GW	18kg/1pc
				Outbox dimension	1253*368*123mm	Outbox GW	18kg/1pc