

LED STREET LIGHT PRODUCT DESCRIPTION

Model	KTSL2003				
Power	50W	80W(2*40W)	100w(2*50W)	150W(3*50W)	200W(4*50W)
Dimension L*W*H(mm)	500*230*80mm	720*280*80mm	720*280*80mm	860*330*80mm	950*350*80mm
Installation Height	5-6M	7-8M	8-10M	8-10M	10-12M
Voltage	AC85-265V	AC85-265V	AC85-265V	AC85-265V	AC85-265V
CCT	2600K/3000K/4000K/6500K	2600K/3000K/4000K/6500K	2600K/3000K/4000K/6500K	2600K/3000K/4000K/6500K	2600K/3000K/4000K/6500K
Luminous flux	130-140LM/W	130-140LM/W	130-140LM/W	130-140LM/W	130-140LM/W
LED Type	Lumileds3030 /Cree3030	Lumileds3030 /Cree3030	Lumileds3030 /Cree3030	Lumileds3030 /Cree3030	Lumileds3030 /Cree3030
LEDs qty	1PCS 50W	2PCS 40W	2PCS 50W	3PCS50W	4PCS50W
LED Driver	LP ,MEANWELL	LP ,MEANWELL	LP ,MEANWELL	LP ,MEANWELL	LP ,MEANWELL
Material	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
Install pole diameter	60mm	60mm	60mm	60mm	60mm
Beam angle	60°	60°	60°	60°	60°
Power factor	>0.98	>0.98	>0.98	>0.98	>0.98
CRI	>80	>80	>80	>80	>80
Lifetime	50000hrs	50000hrs	50000hrs	50000hrs	50000hrs
Warranty	3-5year	3-5years	3-5years	3-5years	3-5years
Certification:	CE&RoHS	CE&RoHS	CE&RoHS	CE&RoHS	CE&RoHS
G.W/kg	3.3KG	3.5KG	4.3KG	6.3KG	7.4KG
Outer Carton/cm	63*27*11CM	74.5*29.5*11.5CM	74.5*29.5*11.5CM	88*33.5*11.5CM	97*36*11.5CM
Qty/Ctn	1set	1set	1set	1set	1set

