

Hunan Kontak Technology Co.,LTD

Room 2402, Skyer City, No 59 Furong Middle Road Second Section, Changsha City, Hunan Province, China

Tel: +86-731-85860892 Email: kontak@kontak-cn.com, Website: www.kontakledlight.com



Solar street light 15w		Model: KTSL8020C-15
Main Lamps material	Aluminium Alloy	
Solar panel	Max Power	18V43W
Battery	li-ion battery	3.7V 192WH
	LiFePO4 battery	3.2V 179WH
LED	Led chip brand	Bridgelux from USA with high brightness
	Lumen(LM)	1500-1650LM
	CCT (k)	6000-7000k
	Life Time	50000 hours
Camera	Pixel	1,100,000 pixel
	Video Compression	Adopt H.264 Main Profile and Baseline profile compression algorithm, Image is more clear, less code flow, be easy to network transmission, and storage space save
	Network function	1, Support the double stream monitor at the same time; 2, Support mobile phone to see; 3, Support 6 users monitor the IP Camera at the same time; 4, Build-in WEB SERVER, Support IE browse and parameter setting, use one port for data transmitting, making it easy for users to network Settings; 5, Support 802.11b/g/n agreement, can be built-in wifi module, Flexible forming wireless monitoring environment; 6, Supports four regional Motion Detection and alarm linkage call presets;
	storage	32G TF card
	Interface	WIFI
	Lighting Viewing Angle	140°×70°
Working TEMP(°C)	-20°~+60°	
Working Mode	Sensing Mode	
Charge time(by sun):	8-10hours (with enough strong shine)	
Discharge time	10-12 hours per night 3-5rainy days	
Certificate	CE/ROHS/IP66	
	Product size	882*315*206 mm



Packing	Packing size	Box 1: 1000*440*190mm (lamp body) Box 2 : 350*290*220mm (Supportor+Accessories)	
	Net weight	11 kg	
	Gross weight	13.5 kg	
	Packing way	1sets/2carton	
Packs Containers	20ft container	290pcs	
	40gp container	590pcs	
Installation height	4-5meters	Suggestion distance	20-25meters

Hunan Kontak Technology Co.,LTD



Room 2402,Skyer City,No 59 Furong Middle Road Second Section,Changsha City,Hunan Province.China
Tel:+86-731-85860892 Email: kontak@kontak-cn.com, Website: www.kontakledlight.com



Solar street light 30W		Model: KTSL8020C-30
Main Lamps material	Aluminium Alloy	
Solar panel	Max Power	18V60W
Battery	li-ion battery	3.7V 303WH
	LiFePO4 battery	3.2V 268WH
LED	Led chip brand	Bridgelux from USA with high brightness
	Lumen(LM)	3000-3300LM
	CCT (k)	6000-7000k
	Life Time	50000 hours
Camera	Pixel	1,100,000 pixel
	Video Compression	Adopt H.264 Main Profile and Baseline profile compression algorithm, Image is more clear, less code flow, be easy to network transmission, and storage space save
	Network function	1,Support the double stream monitor at the same time; 2,Support mobile phone to see; 3,Support 6 users monitor the IP Camera at the same time; 4,Build-in WEB SERVER, Support IE browse and parameter setting, use one port for data transmitting, making it easy for users to network Settings; 5,Support 802.11b/g/n agreement,can be built-in wifi module, Flexible forming wireless monitoring environment; 6,Supports four regional Motion Detection and alarm linkage call presets;
	storage	32G TF card
	Interface	WIFI
Lighting Viewing Angle	140°×70°	
Working TEMP(°C)	-20°~+60°	
Working Mode	Sensing Mode	
Charge time(by sun):	8-10hours (with enough strong shine)	
Discharge time	10-12 hours per night 3-5rainy days	
Certificate	CE/ROHS/IP66	
	Product size	1198*315*206 mm



Packing	Packing size	Box 1: 1310*440*190 mm (lamp body) Box 2 : 350*290*220mm (Supportor+Accessories)	
	Net weight	13.6kg	
	Gross weight	16.9 kg	
	Packing way	1sets/2carton	
Packs Containers	20ft container	230pcs	
	40gp container	470pcs	
Installation height	7-8meters	Suggestion distance	25-30meters

Hunan Kontak Technology Co.,LTD



Room 2402, Skyer City, No 59 Furong Middle Road Second Section, Changsha City, Hunan Province, China

Tel: +86-731-85860892 Email: kontak@kontak-cn.com, Website: www.kontakledlight.com



Solar street light 60W		Model: KTSL8020C-60
Main Lamps material	Aluminium Alloy	
Solar panel	Max Power	18V78W
Battery	li-ion battery	3.7V 388WH
	LiFePO4 battery	3.2V 358WH
LED	Led chip brand	Bridgelux from USA with high brightness
	Lumen(LM)	6000-6600LM
	CCT (k)	6000-7000k
	Life Time	50000 hours
Camera	Pixel	1,100,000 pixel
	Video Compression	Adopt H.264 Main Profile and Baseline profile compression algorithm, Image is more clear, less code flow, be easy to network transmission, and storage space save
	Network function	1,Support the double stream monitor at the same time; 2,Support mobile phone to see; 3,Support 6 users monitor the IP Camera at the same time; 4,Build-in WEB SERVER, Support IE browse and parameter setting, use one port for data transmitting, making it easy for users to network Settings; 5,Support 802.11b/g/n agreement,can be built-in wifi module, Flexible forming wireless monitoring environment; 6,Supports four regional Motion Detection and alarm linkage call presets;
	storage	32G TF card
	Interface	WIFI
Lighting Viewing Angle	140°×70°	
Working TEMP(°C)	-20°~+60°	
Working Mode	Sensing Mode	
Charge time(by sun):	8-10hours (with enough strong shine)	
Discharge time	10-12 hours per night 3-5rainy days	
Certificate	CE/ROHS/IP66	
	Product size	1514*315*206 mm

	Packing	Packing size	Box 1: 1610*440*190 mm (lamp body) Box 2 : 350*290*220mm(Supportor+Accessories)	
		Net weight	16.5kg	
		Gross weight	20.3 kg	
		Packing way	1sets/2carton	
	Packs Containers	20ft container	200pcs	
		40gp container	410pcs	
	Installation height	7-8meters	Suggestion distance	25-30meters