



KTWL-1303D(R)		Single Color		
● Red	LED	1Wx3	90-260V	50/60Hz

KTWL-1303D(G)		Single Color		
● Green	LED	1Wx3	90-260V	50/60Hz

KTWL-1303D(B)		Single Color		
● Blue	LED	1Wx3	90-260V	50/60Hz

KTWL-1303D(Y)		Single Color		
● Yellow	LED	1Wx3	90-260V	50/60Hz

KTWL-1303D(WW)		Single Color		
● Warm White	LED	1Wx3	90-260V	50/60Hz

KTWL-1303D(W)		Single Color		
○ White	LED	1Wx3	90-260V	50/60Hz

KTWL-1303T		RGB(Flash)		
● RGB	LED	3W	175-250V	50/60Hz

KTWL-1303J		RGB(Fade)		
● RGB	LED	3W	175-250V	50/60Hz

KTWL-1303C		RGB(Pre-programmed)		
● RGB	LED	9W	90-260V	50/60Hz



PRODUCTS CHARACTERS:

- Body: Made of high quality die-cast aluminum with treatment of corrosion protection and UV-proof powder coating.
- Diffuser: PMMA.
- Gasketing: Made of thermostable silica gel to improve protection class.
- Fastener: Made of stainless steel with high intensity and corrosion protection.
- Application: Facade lighting, wall of buildings, villas, parks, gardens, hotels and so on.
- Finish: Matt black as standard. Matt red, Matt coffee, Matt grey, Dark grey, Dark bronze any other RAL color is available upon request.

