



SECURITY ANTI CLIMB FENCING SYSTEM



Steel security fencing is suitable for the following applications

- ★ **Correctional Facilities**
- ★ **Detention Centre**
- ★ **Airports Military**
- ★ **Sites Schools Retail**
- ★ **Precincts Business**
- ★ **Precincts Utility**
- ★ **Public Works Facilities**
- ★ **Critical Services Infrastructure**
- ★ **Bridge Security**

High performance, high security 358-mesh fencing is designed for demanding applications as it provides the ultimate protection against anti-climb & cut through.

Manufactured using 4 mm wire and welded at each intersection to create a strong and durable panel, the mesh aperture consists of a 76.2 mm x 12.7 mm spacing that provides excellent see through visibility.

Our goal is to supply the highest quality steel security fencing products, at consistently competitive prices. Our promise is to keep pricing as low as possible to deliver value and satisfaction to the end-user

Specification Data Sheet

Panels		Post			
Fence		Post	Height	Number of Fixings	
Height	Width	Size		Inters	Corners
m	m	mm	m	1 clamp	2 clamp
2.0	2.5	60×60×2.5	2.7	7	14
2.4	2.5	60×60×2.5	3.1	9	18
3.0	2.5	80×80×2.5	3.8	11	22
3.3	2.5	80×80×2.5	4.2	12	24
3.6	2.5	100×60×3	4.5	13	26
3.6	2.5	100×100×3	4.5	13	26
4.2	2.5	100×100×3	5.2	15	30
4.5	2.5	100×100×3	5.5	16	32
5.2	2.5	120×120×3	6.2	18	36

PANELS

Manufactured using 4 mm wire welded at each intersection creating a strong and durable panel, the mesh aperture consists of a 76.2 x 12.7 mm mesh spacing providing ultimate protection against climbing and cut-through with excellent see through visibility. Standard mesh panel width is 2500 mm.

POSTS

Standard posts are manufactured from 60 x 60 up to 2.4 m high, rolled hollow section and include stepping provisions to suit on-site conditions. Standard post centre is 2480 mm. All posts include bolt-through or threaded inserts. Extra length posts can be used to increase the fence heights above standard heights. 60 x 60 x 3 RHS c/w clamp bar and M8 cup square bolts complete with cone nuts through posts.

FIXINGS

Specially designed securing clamp system is used for quick and easy installation. Clamp bar 40 x 5mm - M8 cup square bolts complete with cone nuts. All fixings are tamper-proof and anti-vandal.

Please note: Hole centre on fixing detail can be reduced from 304mm to 152mm for additional security. Post section is determined by the height of the fence

GATES

Standard gates are available or tailored-made to suit your requirements. All gates are supplied with rear hung adjustable hinges, pad-lockable drop-bolts, multi-holed to suit site conditions complete with anti-climb slide latch.