

Filter Series

- Microporous Membrane Filter -

- Flow capacity : 0.5t/h-30t/h
- Filter house length : 5" , 10" , 15" , 20" , 30" etc
- Filter cartridge quantity in filter : 1core ,3core ,5core ,7 core,9core ,11core etc
- Filter house material : 304/316L
- Filter cartridge material : PTFE , PP, PVDF, N66, PES
- Filter precision : 0.22um, 0.4um, 1um, 3um, 5um, 10um, 20um, 50um etc
- Cartridge connection model : 222, 226 etc



- Duplex Filter -

- Filter area : 0.1m²- 0.50m²
- Flow capacity : 1t/h-20t/h
- Aperture of filter screen : 40~400mesh
- Filter material : 304/316L



- Titanium Stick Filter -

Titanium stick filter has the characteristics of high pressure, strong acid, strong alkali, corrosion resistance and recyclable filter element. It is a hollow filter tube made by powder metallurgy without sintering titanium powder at high temperature. It is widely used in liquid-solid separation in food, beverage, medicine and chemical industries. It is especially suitable for large infusion and injection production lines in pharmaceutical industry. Decarbonization filtration.



- Stainless Steel Press Filter -

Model	YL150	YL200	YL300	YL400
Filter Plate Diameter (mm)	150	200	300	400
Plate Number	10			
Pump Flow Capacity (T/h)	1	3	5	8
Pump Motor Power (Kw)	0.75	1.1	1.5	2.2
Dimension L*W*H (mm)	800*600*500	900*650*500	1050*650*500	1200*700*600

*Above model just for reference, we can do according to client's URS *

