



GUANGZHOU QUANJU OZONE TECHNOLOGY CO., LTD

QUANJU TECHNOLOGY (HK) CO., LIMITED

Address: No.2, Hualong Road, Donghua Industrial Zone, Renhe, Baiyun District Guangzhou, 510000, China

Phone: 86-020-36133629

Fax: 86-020-26287681

Website: www.qjzonemade.com

What's the specification of venturi injector?

Model	Size (inch)	Water pressure (Mpa)	inspiratory capacity (M ³ /hr)	Overall length (mm)	Water flow (M3/hr)	Material
A12057	1/4	0.1-0.2	1-3	57	0.05-0.2	PVDF
A25100	1/2	0.25-0.4	4-7	100	0.2-1	PVDF
A25152	3/4	0.25-0.5	7.5-10	152	1—3	PVDF
A32235	1	0.25-0.5	11-15	230	3—10	PVDF
A48275	1.5	0.25-0.6	22-30	275	10—25	PVDF
A58295	2	0.3-0.7	37-49	295	25-50	PVDF



What's the features of venturi injector ?

- ◆ ozone gas mixing device pvdf venturi injector, low flow and small volume, was specially designed for small water treatment products.
- ◆ The unique mixed air chamber design and the strong mixed injection of water and air make the mixing well-distributed, complete, and make the bubbles exquisite, mixed with high efficiency, low energy consumption and long service life.
- ◆ Compact structure, simple maintenance, fast installation, reliable operation, be ready to start or stop at any time and automatic operation.
- ◆ Durable PVDF construction
- ◆ Check valve included in injection port



GUANGZHOU QUANJU OZONE TECHNOLOGY CO., LTD

QUANJU TECHNOLOGY (HK) CO., LIMITED

Address: No.2, Hualong Road, Donghua Industrial Zone, Renhe, Baiyun District Guangzhou, 510000, China

Phone: 86-020-36133629

Fax: 86-020-26287681

Website: www.qjozonemade.com

What's the application of venturi injector ?

- ◆ Small ozone generator support equipments.
- ◆ All kinds of small water treatment gas-water mixing loop

Notices:

- ◆ Water temperature must be 0°C~60°C;
- ◆ Water PH value should be 5~11;
- ◆ Mixed liquid must not be flammable, the length of zonal impurities no longer than 25 cm, diameter of granule impurities less than 4 mm in water.