

WR-T2-AC

For installation at LPZ 0_s-1 or higher, protecting low voltage devices from surge damages, mainly used in power supply system such as power distribution-room, distribution-cabinet and other important power supply system.

Applied in pluggable SPD Class II(Class C)for various power supply system.


Designed according to IEC 61643-1/GB 18802.1.

- Standard single chip structure, pluggable
- Consist of varistor and thermal disconnection device
- High discharge capacity, quick response
- Double thermal disconnection devices, provide more reliable protection
- Multifunctional terminals for connection of conductors and busbars
- Green window will change when fault occurs, also provide remote alarm terminal at the same time




Type	WR-T2-AC	
Rated voltage (max.continuous a.c.voltage) [U _c]	275V or 385V	
Nominal discharge current (8/20) [I _n]	20kA	
Maximum discharge current [I _{max}]	40kA	
Voltage protection level [U _p]	≤1.5kV	
Response time [t _λ]	≤25ns	≤25ns
Max. backup fuse	125A gL/gG	125A gL/gG
Operating temperature range [T _o]	-40°C...+80°C	-40°C...+80°C
Cross-sectional area	1.5mm ² ~ 25mm ² solid / 35mm ² flexible	
Mounting on	35mm DIN rail	
Enclosure material	Purple (module) / light gray (base) thermoplastic, UL94-V0	
Dimension	1 mod	
Test standards	IEC 61643-1; GB 18802.1; YD/T 1235.1	
Certification	CE ROHS ISO9001 CQC TUV	
Type of remote signalling contact	Switching contact	
Switching capacity a.c.	250V/0.5A	
Switching capacity d.c.	250V/0.1A; 125V/0.2A; 75V/0.5A	
Cross-sectional area for remote signalling contact	Max. 1.5mm ² solid/flexible	

Type	WR-T2-AC	
Packing unit	4pc(s)	
Weight	120g	




WR-T2-AC Basic circuit diagram



WR-T2-AC Dimension diagram




WR-T2-AC / 2P



Type	WR-T2-AC / 2P
Packing unit	2pc(s)
Weight	207g




WR-T2-AC / 1+NPE



Type	WR-T2-AC / 1+NPE
Packing unit	2pc(s)
Weight	205g




WR-T2-AC / 3P



Type	WR-T2-AC / 3P
Packing unit	1pc(s)
Weight	303g




WR-T2-AC / 3+NPE



Type	WR-T2-AC / 3+NPE
Packing unit	1pc(s)
Weight	376g



WR-T2-AC / 4P



Type	WR-T2-AC / 4P
Packing unit	1pc(s)
Weight	376g