

Soild Color Epoxy Floor Coating System









Shenzhen Meitaibang Chemical Co.,Ltd

Add: 3/F,Block B,Hengyu Science Park,Nanlian,Longgang,Shenzhen Email: mtb@glue-adhesive.com Tory.liu@glue-adhesive.com Tel: +86-755-84828579 Mob: +86-13682569107



Soild Color Epoxy Floor Coating System

Soild Color Epoxy Floor Coating System is a high build, self leveling, clear or pigmented resinoufls ooring system engineered for industrial applications. This system withstands high impact environments, providing chemical and abrasion resistance. It also has the option to be a applied as a high build product to cover small imperfections. The product is pretinted to ensure a consistent color match every time

The solid color epoxy system offers a wide spectrum of textures and colors, with full custom color matching available. This system is the perfect choice for large projects, and with long open times you can apply a lot of square footage at once.

TYPICAL AREAS OF USE

MTBJZJ® Solid Color Epoxy Floor Coating Systems is intended for floors subject 0.03% to medium to high foot traffic, fork lift and rubber wheel carts.

Typical uses include:

- · Warehouses
- · Manufacturing areas
- · Laboratories & clean rooms
- · Automobile service areas & garages
- $\bullet \ Exhibition \ halls$
- $\bullet \ Medical \ \& \ educational \ facilities$
- $\bullet \, Aircraft \, hangars$
- · Airplane Hangars
- Hospitals
- Warehouses
- Distribution Centers
- Laboratories
- · Manufacturing Facilities
- Parking Decks
- Garages

Features & Benefits

- $\bullet \ Ease \ of \ maintenance$
- Protects the substrate
- Increases the strength of the substrate
- \bullet Hard and abrasion resistant
- VOC free & Non-toxicStain and chemical resistant
- Anti-Slip
- Fast set available for quicker turn around time

- · High loss finish
- Completely UV stable
- 15 standard colors
- Varied traction coefficients available.
 All-climate application down to-30° F
- Excellent color/gloss retention
- · Low-emitting, green friendly options

Coverage Data


MTB-3327 Epoxy Primer, @1mm, 0.15kgs/m²
MTB-3328 Epoxy Middle Coat, @2mm, 0.75kgs/m²
MTB-3329 Epoxy Top Coat, @1mm, 0.15kgs/m² Solid Color Pigments, 0.015kgs/m²

SAMPLE COLOR CHART



Operation of Solid Color Epoxy Floor Coating

For the whole process of the using process, please refers to below diagram and the tips.





MTB-3327 Epoxy Primer



MTB-3328 Epoxy Middle Coat



MTB-3329 Epoxy Top Coat