

OHQ-0309 directional coupler

Using the stripline structure, OHQ-0309 series directional coupler has good flatness inside strip. It has high isolation, less insertion loss, good VSWR and easy to install. It can be used in indoor coverage system for cellular mobile communication and spread spectrum communication.

Specifications			
Model	OHQ-6-0309	OHQ-10-0309	OHQ-15-0309
Freq. Range-MHz	350~870		
Coupling Level-dB	6 ± 1	10 ± 1.5	15 ± 1.5
Insertion Loss-dB	≤ 1.8	≤ 1.0	≤ 0.5
Isolation-dB	≥ 20		
VSWR	≤ 1.4		
Nominal Impedance- Ω	50		
Max. Power-W	50		
Connector Type	N Female or Customization		
Temperature Range- $^{\circ}\text{C}$	$-30 \sim +60$		
Relative Humidity-%	5~95		
Size-mm	126x34x16		
Weight-g	210		



KENBOTONG TECHNOLOGY CO., LTD.

Add: NO.2 Chanxiu Road, Foshan City, Guangdong China Code:528061

Tel: 86(757)8202-5597 8221-9788

Fax: 86(757)8221-2072,8802-2808

E-mail:kbt@kenbotong.com

<http://www.kenbotong.com>