

**KBT**

2350-2550MHz 7dBi Fiberglass Omni Antenna

TQJ-2325G7F26

Applications

2350-2550MHz Band Communications/ Wireless Data transmission System/ Wireless Paging System.


Electrical Specifications

Frequency Range (MHz)	2350~2550
Bandwidth(MHz)	200
Polarization	Vertical
Gain (dBi)	7
Horizontal Beam Width(°)	360
Vertical Beam Width(°)	22±5
Horizontal unroundness(dB)	±1.5
Impedance (Ω)	50
VSWR	≤1.5
Maximum Input Power (W)	200


Mechanical Specifications

Connector Type	N Male
Connector Position	Bottom
Antenna Size (mm)	φ 29* (600±5)
Antenna Weight (Kg)	0.281±0.05
Radome material	Fiberglass
Radome color	White@Fiberglass
Operating Temperature (°C)	-40~+70
Relative Humidity(%)	5~95
Rated Wind Velocity (m/s)	55
Salt Spray Resistance	96Hour Neutral (GB/T 2423.17-2008)
waterproofing grade	IP65
Applications	Outdoor
Mounting	The Antenna can be directly connected to the device

Typical pattern E Plane



Typical pattern H Plane



Add: No.30 Dongyang 3rd Road, Danzao Town, Nanhai District, Foshan City, Guangdong, China 528216

Tel: +86-757-88022860

Email: kbt@kenbotong.com

Web: <http://www.kenbotong.com>




KBT

2350-2550MHz 7dBi Fiberglass Omni Antenna

Product Pictures



Installation Sketch



Add: No.30 Dongyang 3rd Road, Danzao Town, Nanhai District, Foshan City, Guangdong, China 528216

Tel: +86-757-88022860

Email: kbt@kenbotong.com

Web: <http://www.kenbotong.com>