

**KBT**

2380-2520MHz 8dBi Fiberglass Omni Antenna

TQJ-2325G8F20U3

Applications

2.4GHz Band Communications/ Wireless Data transmission System/ Wireless Paging System.


Electrical Specifications

Frequency Range(MHz)	2380~2520
Bandwidth(MHz)	140
Polarization	Vertical
Gain(dBi)	8
Horizontal Beam Width(°)	360
Vertical Beam Width(°)	14
Electrical UP (°)	3
Horizontal unroundness(dB)	± 1.5
Impedance (Ω)	50
VSWR	≤ 1.8 (MAX)
Maximum Input Power(W)	200


Mechanical Specifications

Connector Type	N Male
Connector Position	Bottom
Antenna Size (mm)	$\phi 24^* (600 \pm 5)$
Antenna Weight (g)	230 ± 50
Radome material	Fiberglass
Radome color	Gray or Black@Fiberglass(or Customized)
Operating Temperature(°C)	$-40 \sim +70$
Relative Humidity(%)	5~95
Rated Wind Velocity(m/s)	55
Salt Spray Resistance	96Hour Neutral (GB/T 2423.17-2008)
waterproofing grade	IP65
Applications	Outdoor
Mounting	mounting with piggyback device

Typical pattern E Plane



Typical pattern H Plane



Add: No.30 Dongyang 3rd Road, Danzao Town, Nanhai District, Foshan City, Guangdong, China 528216

Tel: +86-757-88022860

Email: kbt@kenbotong.com

Web: <http://www.kenbotong.com>




KBT

2380-2520MHz 8dBi Fiberglass Omni Antenna

Product Pictures



Installation Sketch



Add: No.30 Dongyang 3rd Road, Danzao Town, Nanhai District, Foshan City, Guangdong, China 528216

Tel: +86-757-88022860

Email: kbt@kenbotong.com

Web: <http://www.kenbotong.com>