KBT 820～894MHz 11dBi Fiberglass Omni-directional Antenna

TQJ-800AII-M

Application

Used in: Wireless Data transmission system/Wireless Paging System

Electrical Specifications	
Frequency Range (MHz)	820～894
Polarization	Vertical
Gain (dBi)	11
Horizontal Beam Width (°)	360
Vertical Beam Width(°)	7
Impedance (Ω)	50
VSWR	≤1.5
Intermo Dulation IM3 (2×43dBm carrier)	≤-150 dBc
Maximum Power (W)	300
Ground Protection	DC Grounding
Mechanical Specifications	
Connector Type	7/16DIN-K
Connector Position	Bottom
Depth/ Height (mm)	Φ60*（3160±5）
Packing Size (mm)	3310*110*120
Weight (kg)	4±0.2(exclude the bracket)
Radome Material	Fiberglass
Radome Color	White
Operating Temperature (℃)	-40～65
Relative Humidity%	5～95
Rated wind Velocity (m/s)	60
Ingress Protection	IP24（IP65 Test without blocking water outlet）
Applications	Outdoor
Uitable pole Diameter (mm)	Mast(Mast Supplied by customer, Φ40- Φ50)
Mounting Kit	JM-1UI or JM-1DB

Typical pattern

820～894MHz E Plan



820～894MHz H Plan



No.2 Chanxiu Road, Foshan, Guangdong, China. 528061 Tel: +86-757-82219788 Fax: +86-757-82212072
Email: kbt@kenbotong.com Web: http://www.kenbotong.com

820～894MHz 11dBi Fiberglass Omni-directional Antenna

Product Picture

Product Size



Installation Sketch





No.2 Chanxiu Road, Foshan, Guangdong, China. 528061 Tel: +86-757-82219788 Fax: +86-757-82212072
Email: kbt@kenbotong.com Web: http://www.kenbotong.com