REBO

D-Series













REBO BAMBOO PRODUCTS

All Bamboo decking in the photo are FSC®-certified














REBO focus on bamboo outdoor decking's optimization and upgrading, aims on green, eco-friend, health. It will be the excellent replacement of WPC and traditional woods due to its superior durability, safety and other physical properties

Outdoor Decking Appearance



1850mm (72-7/8") X 140mm (5-1/2") X 20mm (3/4+")


1850mm

Quality


Moisture content	6-15%
4h Circulating boiled thickness expansion ratio	≤5%
72h Thickness expansion ratio	≤10%
Density	1.2g/cm ³

Technical Data

Test Items	Test Results	Testing Standard	
Brinell hardness	107N / mm²	EN 1534 : 2011	
Bending strength	87N / mm ²	EN 408 : 2012	
Modulus of elasticity in bending (mean value)	18700N / mm²	EN 408 : 2012	
Durability	Class 1 / ENV807 ENV12038	EN350	
Use class	Class 4 (Class 5 first year performing well)	EN335	
Reaction to fire	Bfl-s1	EN13501-1	
Slip resistance (Oil-wet ramp test)	R10	DIN 51130:2014	
Slip resistance (PTV20)	86(Dry), 53(Wet)	CEN/TS 16165: 2012 Annex C	



REBO Cladding has high durability (Durability Class1- ENV12038), fire prevention (Bfl-s1), moth proofing and other characteristics. To look better and fashion of outdoor decoration, REBO Cladding will be your great choice.





With REBO bamboo planks will enhance the spatial design of urban facilities show and spread the concise, generous, ecological and natural image of city. It's ideal material for convenient bench, city flower column, beam, fence and horse stable planks etc.

REBO Planks are available in following specifications:



1860mm X 40mm X 40mm



1860mm X 60mm X 40mm



1860mm X 100mm X 30mm



1860mm X 140mm X 40mm

For other customizations, please contact us.

Disclaimer

REBO products will only applies to the normal environment and use conditions of buildings. It does not include the damage caused by misuse, accident, natural disaster and force majeure, damage caused by obvious surface nick or destroy or erection joint, chromatic aberration caused by illumination, natural oil loss of surface caused by seasonal climatic variation, or damage caused by improper installation, maintenance, cleaning, surface paint care, mechanical or chemical contamination.

The strand woven bamboo is a natural forest product, with differences in color, texture and surface. The color may change based on the maintenance period and service time. The surface and end face may produce small cracks due to their different air shrinkage bulking factors. The surface may become coarse after a certain period of time, due to the constant expansion and contraction caused by different local temperatures and climate changes. The product may have slight dimensional changes or produce a tile-shaped deformation after installation.

The manufacturer cannot be held liable for these phenomenon.



After Installation

After 2 years of use

After cleaning

After maintenance


Comparison with other similar products


Material	Natural wood	Anticorrosive timber	Carboinzed timber	WPC	REBO DECKING
Corrosion resistance	***	***	***	**	****
Anti mildew	***	***	***	***	****
Stability	Easy orack Easy deformation	Easy crack Easy deformation	Easy crack	Easy deformation	Extremely stable
Hardness	***	**	*	**	****
Termite resistance	**	*	*	***	****
Reaction to fire	С	С	С	С	Bf1-s1
Use period	5-8years	3-8years	6-8years	3-6years	over 15 years



sales@fjgoldenbamboo.com








No.175, National Rd. 319, Nanjing High-Tech Zone, Zhangzhou, Fujian, China 303601



Ask/look for our FSC®-certified products

FUJIAN GOLDEN BAMBOO INDUSTRY CO.,LTD.

Projects Reference





Minhang District Alibaba Center, Shanghai





