

NO.813 SELF TRADE BUILDING F.T.Z. DALIAN CHINA

Material Safety Data Sheet CMIT/MIT 14M

1. Identification of the substance/mixture and of the company/undertaking

Product Name:	CMIT/MIT 14M	
Chemical Name:	5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE	
Application :	Industrial Microbicide	
Uses advised against	No further relevant information available.	
Supplier details:		
Company name: SINOTRUST CHEMICAL CO. LTD		
Add: NO.813 SELF TRADE BUILDING F.T.Z. DALIAN CHINA		
TEL: 0086-139 9868 314	5 Email: sales@sinotrustchemical.com	
Emergencies phone: 0086-139 9868 3145		

2. Hazards identification

Classification of the substance or mixture

Classification and labelling according Regulation (EC) No 1272/2008 [CLP]

Classification

Acute toxicity, Oral (Category 4), Acute toxicity, Inhalation (Category 5) Acute toxicity, Dermal (Category 3) Skin corrosion (Category 1A), Serious eye damage (Category 1) Acute aquatic toxicity (Category 1) Chronic aquatic toxicity (Category 1)

Label elements Hazard pictograms







Signal wordDangerHazard-determining components5-Chloro-2-methyl-4-isothiazolin-3-one/2-methyl-4-isothiazolin-3-one 2.5%Of labelling:H302: Harmful if swallowed.

H311: Toxic if contact with skin.

- H314: Cause severe skin burns and eye damage.
- H317: May cause an allergic skin reaction.



NO.813 SELF TRADE BUILDING F.T.Z. DALIAN CHINA

H331:	Toxic if inhaled.
-------	-------------------

H410: Toxic to aquatic life with long lasting effects.

Precautionary statements

P280: Wear protective gloves/protective clothing/eye protection/face protection.
P303/P361/P353: If on skin (or hair):Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305/P351/P338: If in eyes: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
P314: Get medical advice/attention if you feel unwell.
P391/P501: Collect spillage/Dispose of contents/container.

Supplemental Hazard Statements NONE.

3. Composition/information on ingredients

Chemical characterization Component	Mixtures	
26172-55-4	5-Chloro-2-methyl-4-isothiazolin-3-one	10.0-12.0%
2682-20-4	2- methyl-4-isothiazolin-3-one	3.0-5.0%
7647-14-5	Sodium chloride	6.0-8.0%
7631-99-4	Sodium nitrate	18.0-22.0%
7732-18-5	Water	Balance

4. First- aid measures

Description of first aid meas	ures
Inhalation	Move subject to fresh air.
Eye Contact	Immediately flush eyes with a large amount of water for at least 15minutes. Get prompt medical attention.
Skin Contact	Wash affected skin areas thoroughly with soap and water immediately after exposure. Remove and wash contaminated clothing thoroughly. Do not take clothing home to be laundered. Discard contaminated shoes, belts and other articles made of leather. Get prompt medical attention.
Ingestion	If swallowed, give 2 glasses of water to drink. Immediately see a physician. Never give anything by mouth to an unconscious person.
Most important symptoms and effects, both acute delayed	Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special and treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.
Note to Physician	Material is corrosive. It may not be advisable to induce vomiting. Possible mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock and convulsions maybe necessary.



NO.813 SELF TRADE BUILDING F.T.Z. DALIAN CHINA

Extinguishing media Suitable extinguishing agents	Water spray jet, extinguishing powder, CO2, foam.
Fire / Explosion Hazards	During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.
Special hazards arising from the substance or mixture	Nitrogen oxides (NOx) ,Sulphur oxides ,Hydrogen chloride
Advice for firefighters Further information	Wear self-contained breathing apparatus and protective suit. Cool containers / tanks with water spray. Minimize exposure. Do not breathe fumes.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Wear respiratory protection. Avoid dust formation. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. Protective clothing, including chemical splash goggles, nitrile or butyl rubber full length gloves, rubber apron, or clothing made of nitrile or butyl rubber, and rubber overshoes must be worn during spill clean-ups and deactivation of this material. If material comes in contact with the skin during clean-up operations, immediately remove all contaminated clothing and wash exposed skin areas with soap and water.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.
Methods and material for containment and cleaning up	Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

See section 13 for further information.

7. Handling and storage

Precautions for safe handling	Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Provide appropriate exhaust ventilation at places where dust is formed.
	Normal measures for preventive fire protection.
Conditions for safe storage,	The maximum recommended storage temperature for this material is
including any incompatibilities	55°C/131F. The minimum recommended storage temperature for this material is 1°C/32F. Store in a well ventilated area. Do not store this material in containers made of the following: steel.
Incompatible Materials for Storage	Reducing agents, oxidizers, amines, mercaptans.

8. Exposure controls/personal/protectio



NO.813 SELF TRADE BUILDING F.T.Z. DALIAN CHINA

Engineering Controls	Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Use local exhaust ventilation with a minimum capture velocity of 150 ft/min. (0.75 m/sec.) at the point of dust or mist evolution. Refer to the current edition of Industrial Ventilation: A Manual of Recommended Practice published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.
Personal protective equipment Eye/face protection	Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).
Skin protection	 Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. The gloves listed below provide protection against permeation: Nitrile /Butyl rubber. The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.
Body Protection	Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Respiratory protection	Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).
Other protective equipment Other protective equipment	Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

9. Physical and chemical properties

a) Appearance: Form: Liquid	b) Odor: Pungent d) pH-value: 2.0-4.0	c) Odour threshold: No data available e) Melting point: -33° C (-27.4 °F)
Color: Pale yellow to amber		
f) Boiling point/Boiling range: 100°C (212.00 °F) Water	g) Flash point: Not applicable	 h) Evaporation rate: <1.0 (n-Butyl acetate=1)



NO.813 SELF TRADE BUILDING F.T.Z. DALIAN CHINA

i) Flammability (solid, liquid):	j) Upper/lower flammability or early a state of the state	xplosive limits: Not applicable
Not applicable		
k) Vapor pressure: No data	l) Vapour density: Not applicable	m) Relative density: 1.15-1.30 g/mL
n) Water solubility: soluble	o) Partition coefficient (Kow):	p) Autoignition temperature:

Not Determined

Not applicable

s) Explosive properties:

No an explosion hazard

- q) Decomposition temperature:r) Viscosity: Not DeterminedNot Determined
- Other information : No further relevant information available.

10. Stability and reactivity

Reactivity	No data available	
Instability	This material is considered stable under specified conditions of	
	storage, shipment and/or use. See section 7, Handling and storage,	
	for specified conditions.	
Possibility of hazardous reactions	No dangerous reactions known.	
Thermal decomposition /	Stable under recommended storage conditions.	
Conditions to be avoided	Product will not undergo polymerization.	
Incompatibility	Avoid contact with the following: oxidizing agents , reducing	
	agents, amines, mercaptans.	
Hazardous decomposition products	Nitrogen oxides (NOx), sulphur oxides, hydrogen chloride.	

11. Toxicological information

Product animal toxicity	
Acute oral toxicity	LD50 ,Rat: 457 mg/kg
Acute inhalation toxicity	Rat, 4h: 0.33mg/L Active ingredient
Acute dermal toxicity	LD50 Dermal Rabbit: 660 mg/kg
Skin irritation	Rabbit, Corrosive (product)
Eye irritation	Rabbit, Corrosive (product)
Respiratory or skin sensitization	May cause sensitization by skin contact.
Carcinogenicity	Non- carcinogenicity. This chemical is not known or reported to be carcinogenic by any reference source including IARC, OSHA, NTP, or E EPA.
Mutagenicity	Collective data indicate non-mutagenic.
Teratogenicity	Not teratogenic
Sensitization	Skin sensitizer.
Acute toxicity	This product is corrosive to all tissues contacted and upon inhalation, may cause irritation to mucous membranes and respiratory tract.
Chronic toxicity	Not known or reported to cause subchronic or chronic toxicity.
Reproductive and	This chemical has been tested in laboratory animals and there was no
Developmental Toxicity:	evidence of reproductive toxicity, teratogenicity, or developmental toxicity.



NO.813 SELF TRADE BUILDING F.T.Z. DALIAN CHINA

12. Ecological information

Biodegradability	CAS # 26172-55-4t 1/2 anaerobic = 4.8 h, CAS # 26172-55-4t 1/2 aerobic = 17.3h, CAS # 2682-20-4 t 1/2 aerobic = 9.1h
Physico-chemical removability Ecotoxicity effects	Activated Sludge Respiration Inhibition EC50: 4.5 mg/ L ai
Toxicity to fish	LC50 Oncorhynchus mykiss (rainbow trout) 96 h 0.19 mg/L Active ingredient
Toxicity to fish	LC50 Lepomis macrochirus (Bluegill sunfish) 96 h 0.28 mg/L Active ingredient
Toxicity to algae	EC50 Marine algae (Skeletonema costatum) 0.003 mg/L Active ingredient
Toxicity to algae	EC50 algae (Selenastrum capricornutum) 0.018 mg/L Active ingredient
Toxicity to aquatic invertebrates	EC50 Daphnia magna 48 h 0.16 mg/L Active ingredient

13. Disposal considerations

Methods of disposal	When a decision is made to discard this material as supplied, it is classified as a RCRA hazardous waste with the characteristic of corrosive.Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations (See 40 CFR 268). Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed prrofessional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.
Contaminated packaging	Dispose of as unused product.

14. Transport information

DOT

DOI	
Proper shipping name	Corrosive, liquid, toxic, n.o.s. (5-Chloro-2-methyl-4-isothiazolin-3-one)
UN-Number	UN 2922
Class	8/6.1
Packing group	II
IMO/IMDG	
Proper shipping name	Corrosive, liquid, toxic, n.o.s. (5-Chloro-2-methyl-4-isothiazolin-3-one)
UN-Number	UN 2922
Class	8/6.1
Packing group	II
IATA-DGR	
Proper shipping name	Corrosive, liquid, toxic, n.o.s. (5-Chloro-2-methyl-4-isothiazolin-3-one)
UN-Number	UN 2922



NO.813 SELF TRADE BUILDING F.T.Z. DALIAN CHINA

Class Packing group

Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations

15. Regulatory information

The following statutes, regulations and standards have the related prescribes on chemicals in terms of safe use, storage, transportation, loading and unloading, classification and symbol etc. Provisions on the Environmental Administration of New Chemical Substances. The Regulation on Chemicals Safe Use at Working Site Law on Prevention and Control of Environmental Pollution Caused by Solid Waste. The rule on dangerous chemicals safety management General rule of classification and hazard communication of chemicals (GB 13690) Occupational Exposure Limits for Hazardous Agent in The workshop Chemical Hazardous Agents(GBZ 2.1). Classification and Code of Dangerous Goods (GB 6944)

List of Dangerous Goods (GB 12268)

China. Inventory of Existing Chemical Substances in China (IECSC):

8/6.1

Π

All intentional components are listed on the inventory, are exempt, or are supplier certified

For professional users only.

EU. EINECS(EINECS): This product satisfies all the requirements of the European Inventory of Existing

Chemical Substances (EINECS).

US. Toxic Substances Control Act (TSCA) : This product is subject to regulation under the US Federal Insecticide, Fungicide and Rodenticide Act (FIFRA) and is therefore exempt from U.S. Toxic Substances Control Act (TSCA) Inventory listing requirements.

16. Other information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CAS	Chemical Abstracts Service (Registry Number)
NIOSH	National Institute for Occupational Safety and Health
OSHA	Occupational Safety and Health Administration
LC50	LC stands for lethal concentration. LC50 is the concentration of a material in air
	which causes the death of 50% (one half) of a group of test animals.
LD50	LD stands for Lethal Dose. LD50 is the amount of a material, given all at once,
	which causes the death of 50% (one half) of a group of test animals

Abbreviations and acronyms

* Data compared to the previous version altered.