

NO.813 SELF TRADE BUILDING F.T.Z. DALIAN CHINA

Material Safety Data Sheet

1. Identification of the substance/mixture and of the company/undertaking

Product Name: CMIT/MIT-1.5 CG
Application: Industrial Microbicide

Supplier details:

Company name: SINOTRUST CHEMICAL CO. LTD

Add: NO.813 SELF TRADE BUILDING F.T.Z. DALIAN CHINA TEL: 0086-139 9868 3145 Email: sales@sinotrustchemical.com

Emergencies phone: 0086-139 9868 3145

2. Hazards Identification:

Classification of the substance or mixture

Classified as hazardous according to regulatory criteria.

Acute toxicity - Category 5 - Oral

Skin corrosion - Category 1B

Serious eye damage - Category 1

Skin sensitisation - Category 1

Acute aquatic toxicity - Category 1

Chronic aquatic toxicity - Category 1

Label elements

Hazard pictograms







Signal word

nghai word Da

Hazard-determining components

of labelling

Hazard statements

Danger

5-Chloro-2-methyl-4-isothiazolin-3-one/4-isothiazolin-3-one 1.5%

H303: May be harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

H410: Very toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

Wear protective gloves/ protective clothing/ eye protection/ face protection.



NO.813 SELF TRADE BUILDING F.T.Z. DALIAN CHINA

Response

IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

Specific treatment (see supplemental first aid instructions on this label).

If skin irritation or rash occurs: Get medical advice/ attention.

Wash contaminated clothing before reuse.

Collect spillage.

Storage Store locked up.

Disposal Dispose of contents/ container to an approved waste disposal plant.

Other hazards No data available.

3. Composition/information on ingredients

Chemical characterization: Mixtures

Description: 5-chloro-2-methyl-2H-isothiazol-3-one and

2-Methyl-4-isothiazolin-3-one

Component:

CAS#	Component	Amount
26172-55-4	5-chloro-2-methyl-2H-isothiazol-3-one	1.0-1.6%
2682-20-4	2-Methyl-4-isothiazolin-3-one	0.3-0.5%
7786-30-3	Magnesium chloride	0.7-0.8%
10377-60-3	Magnesium nitrate	20-25%
7732-18-5	Water	Balance

^{*} All concentrations are percent by weight.

4. First-aid measures

Description of first aid measures

Inhalation Move subject to fresh air.

Eye Contact Immediately flush eyes with a large amount of water for at least 15minutes.

Get prompt medical attention.

Skin Contact Wash affected skin areas thoroughly with soap and water immediately after exposure.

Remove and wash contaminated clothing thoroughly. Do not take clothing home to be laundered. Discard contaminated shoes, belts and other articles made of leather.

Get prompt medical attention.

Ingestion If swallowed, give 2 glasses of water to drink. Immediately see a physician.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute

and effects, both acu

and delayed

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in

Section 11: Toxicology Information.

Note to Physician Material is corrosive. It may not be advisable to induce vomiting. Possible mucosal

damage may contraindicate the use of gastric lavage. Measures against circulatory

shock and convulsions maybe necessary.



NO.813 SELF TRADE BUILDING F.T.Z. DALIAN CHINA

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing agents Water spray jet, extinguishing powder, CO₂, foam.

During a fire, irritating and highly toxic gases may be generated by thermal Fire / Explosion Hazards

decomposition or combustion.

Special hazards arising from the substance or mixture

Nitrogen oxides (NO_x) ,Sulphur oxides ,Hydrogen chloride

Wear self-contained breathing apparatus and protective suit. Advice for firefighters

Further information Cool containers / tanks with water spray. Minimize exposure.

Do not breathe fumes.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Wear respiratory protection. Avoid dust formation. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. Protective clothing, including chemical splash goggles, nitrile or butyl rubber full length gloves, rubber apron, or clothing made of nitrile or butyl rubber, and rubber overshoes must be worn during spill clean-ups and deactivation of this material. If material comes in contact with the skin during clean-up operations, immediately remove all contaminated clothing and wash exposed skin areas with soap and water.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter

drains. Discharge into the environment must be avoided.

Methods and material for containment and cleaning up Pick up and arrange disposal without creating dust. Sweep up and shovel.

Keep in suitable, closed containers for disposal.

See section 13 for further information.

7. Handling and storage

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Precautions for safe handling

Provide appropriate exhaust ventilation at places where dust is formed.

Normal measures for preventive fire protection.

Conditions for safe storage, including any incompatibilities The maximum recommended storage temperature for this material is 55°C/131F. The minimum recommended storage temperature for this

material is 1 oC /32F. Store in a well ventilated area. Do not store this material

in containers made of the following: steel.

Incompatible Materials for Storage: Reducing agents, oxidizers, amines, mercaptans.

8. Exposure controls/personal/protection

Control parameters Components with workplace control parameters

Engineering Controls Avoid contact with skin, eyes and clothing. Wash hands before breaks and

> immediately after handling the product. Use local exhaust ventilation with a minimum capture velocity of 150 ft/min. (0.75 m/sec.) at the point of dust or mist

evolution. Refer to the current edition of Industrial Ventilation: A Manual of



NO.813 SELF TRADE BUILDING F.T.Z. DALIAN CHINA

Recommended Practice published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

Personal protective equipment

Eye/face protection Face shield and safety glasses Use equipment for eye protection tested and

approved under appropriate government standards such as NIOSH (US) or EN

166(EU).

Skin protection Handle with gloves. Gloves must be inspected prior to use. Use proper glove

removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with

applicable laws and good laboratory practices. Wash and dry hands. The gloves listed below provide protection against permeation:

Nitrile /Butyl rubber.

The selected protective gloves have to satisfy the specifications of EU Directive

89/686/EEC and the standard EN 374 derived from it.

Body Protection Complete suit protecting against chemicals, The type of protective equipment

must be selected according to the concentration and amount of the dangerous

substance at the specific workplace.

Respiratory protection Where risk assessment shows air-purifying respirators are appropriate use a full-

face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges

as a backup to engineering controls. If the respirator is the sole means of

protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US)

or CEN (EU).

Other protective equipment Facilities storing or utilizing this material should be equipped with an eyewash

facility and a safety shower.

9. Physical and chemical properties

Information on basic physical and chemical properties

General Information

Form: Liquid

1) 11 1 2050

b) Odor: Mild, inoffensive odor c) Odour threshold: No data available

Color: Colorless or Pale Yellow

a) Appearance:

d) pH-value: 2.0-5.0

e) Melting point: -13°C

Color. Colorless of Pale Yellow

f) Boiling point/Boiling range: 100 °C (212 °F) Water

g) Flash point: Not Determined

h) Evaporation rate:Not Determined

i) Flammability (solid, liquid):

.

j) Upper/lower flammability or explosive limits: Not applicable

Not applicable k) Vapor pressure: No data

1) Vapour density: 0.6 (Air=1)

m) Relative density: 1.10 -1.22 g/mL

n) Water solubility: soluble

o) Partition coefficient (*K*_{ow}): Not Determined

p) Autoignition temperature: Not applicable

q) Decomposition temperature:Not Determined

r) Viscosity:
Not Determined

s) Explosive properties: No an explosion hazard

t) Percent volatility: 95-96%

Other information: No further relevant information available.

The physical data presented above are typical values and should not be construed as a specification.



NO.813 SELF TRADE BUILDING F.T.Z. DALIAN CHINA

10. Stability and reactivity

Reactivity No data available

Instability This material is considered stable under specified conditions of storage,

shipment and/or use. See section 7, Handling and storage, for specified

conditions.

Possibility of hazardous reactions No dangerous reactions known.

Thermal decomposition / Stable under recommended storage conditions. Conditions to be avoided Product will not undergo polymerization.

Incompatibility Avoid contact with the following:

oxidizing agents ,reducing agents ,amines , mercaptans.

Hazardous decomposition products: Nitrogen oxides (NOx), sulphur oxides, hydrogen chloride.

11. Toxicological information

Product animal toxicity

Acute oral toxicity LD50, rat, female, 3,310mg/kg

LD50, rat, male, > 5,000mg/kg

Acute inhalation toxicity LC50, rat, 4 Hour, dust/mist, > 5 mg/l Estimated.

Acute dermal toxicity

Skin irritation

Eye irritation

Rabbit , Corrosive (product)

Rabbit , Corrosive (product)

Sensitization

Guinea pig, Causes sensitization.

Specific Target Organ Product test data not available.

Systemic Toxicity (Single Exposure)

Specific Target Organ Product test data not available.

Systemic Toxicity (Repeated Exposure)

Carcinogenicity Non- carcinogenicity. This chemical is not known or reported to be

carcinogenic by any reference source including IARC, OSHA, NTP, or E

EPA.

Mutagenicity Collective data indicate non-mutagenic.

Teratogenicity Not teratogenic.

Aspiration Hazard Product test data not available.

Chronic toxicity Not known or reported to cause subchronic or chronic toxicity

Reproductive and This chemical has been tested in laboratory animals and there was no

Developmental Toxicity: evidence of reproductive toxicity, teratogenicity, or developmental toxicity.

12. Ecological information

Biodegradability CAS # 26172-55-4t 1/2 anaerobic = 4.8 h, CAS # 26172-55-4t 1/2

aerobic = 17.3h, CAS # 2682-20-4 t 1/2 aerobic = 9.1h

Physico-chemical removability Activated Sludge Respiration Inhibition EC50: 4.5 mg/L ai

Ecotoxicity effects



NO.813 SELF TRADE BUILDING F.T.Z. DALIAN CHINA

Toxicity to fish

LC50 Oncorhynchus mykiss (rainbow trout) 96 h 0.19 mg/L Active ingredient

LC50 Lepomis macrochirus (Bluegill sunfish) 96 h 0.28 mg/L Active ingredient

Toxicity to algae

EC50 Marine algae (Skeletonema costatum) 0.003 mg/L Active ingredient

Toxicity to algae

EC50 algae (Selenastrum capricornutum) 0.018 mg/L Active ingredient

Toxicity to aquatic invertebrates EC50 Daphnia magna 48 h 0.16 mg/L Active ingredient

13. Disposal considerations

Methods of disposal When a decision is made to discard this material as supplied, it is classified as a

RCRA hazardous waste with the characteristic of corrosive.Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations (See 40 CFR 268). Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed prrofessional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn

in a chemical incinerator equipped with an afterburner and scrubber.

Contaminated packaging Dispose of as unused product.

14. Transport information

DOT

Proper shipping name Corrosive, liquid, toxic, n.o.s. (5-Chloro-2-methyl-4-isothiazolin-3-one)

UN-Number UN 2922 Class 8(6.1) Packing group II

IMO/IMDG

Proper shipping name Corrosive, liquid, toxic, n.o.s. (5-Chloro-2-methyl-4-isothiazolin-3-one)

UN-Number UN 2922 Class 8(6.1) Packing group II

Marine pollutant 5-Chloro-2-methyl-4-isothiazolin-3-one

Warranty of Test "Recommendations on the Transport of Dangerous Goods book"

((Revision 18, UN)

"International Maritime Dangerous Goods Code" (2012, IMO)

"List of Hazardous Chemicals" (2002, China)

Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations

15. Regulatory information

The following statutes, regulations and standards have the related prescribes on chemicals in terms of safe use, storage, transportation, loading and unloading, classification and symbol etc.

Provisions on the Environmental Administration of New Chemical Substances.

The Regulation on Chemicals Safe Use at Working Site

Law on Prevention and Control of Environmental Pollution Caused by Solid Waste.

The rule on dangerous chemicals safety management

General rule of classification and hazard communication of chemicals (GB 13690)



NO.813 SELF TRADE BUILDING F.T.Z. DALIAN CHINA

Occupational Exposure Limits for Hazardous Agent in The workshop Chemical Hazardous Agents (GBZ 2.1).

Classification and Code of Dangerous Goods (GB 6944)

List of Dangerous Goods (GB 12268)

China. Inventory of Existing Chemical Substances in China (IECSC):

All intentional components are listed on the inventory, are exempt, or are supplier certified

For professional users only.

EU. EINECS(EINECS): This product satisfies all the requirements of the European Inventory of Existing Chemical Substances (EINECS).

US. Toxic Substances Control Act (TSCA): This product is subject to regulation under the US Federal Insecticide, Fungicide and Rodenticide Act (FIFRA) and is therefore exempt from U.S. Toxic Substances Control Act (TSCA) Inventory listing requirements.

16. Other information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Abbreviations and acronyms

CAS: Chemical Abstracts Service (Registry Number)

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety and Health Administration

LC50: LC stands for lethal concentration. LC50 is the concentration of a

material in air which causes the death of 50% (one half) of a group of test animals

LD50: LD stands for Lethal Dose. LD50 is the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals.

*Data compared to the previous version altered.