

NO.813 SELF TRADE BUILDING F.T.Z. DALIAN CHINA

Material Safety Data Sheet

Section 1 Identification of the substance/mixture and of the company/undertaking

Product Name: OIT-98

Application: Industrial Microbicide

Uses advised against: No further relevant information available.

Supplier info:

Company name: SINOTRUST CHEMICAL CO. LTD

Add: NO.813 SELF TRADE BUILDING F.T.Z. DALIAN CHINA TEL: 0086-139 9868 3145 Email: sales@sinotrustchemical.com

Emergencies phone: 0086-139 9868 3145

Section 2 Hazards identification

Classification of the substance or mixture

Classification according to Regulation (EC) No1272/2008 [GHS/CLP]

Acute toxicity, Oral(Category4), H302

Acute toxicity, Inhalation(Category3) , H331

Acute toxicity, Dermal(Category3), H311

Skin corrosion (Category1B), H314

Skin sensitization (Category1), H317

Acute aquatic toxicity (Category1), H400

Chronic aquatic toxicity (Category1), H410

Label elements

Labelling according Regulation (EC)No1272/2008[CLP]

Hazard pictograms







Signal word Danger

Hazard statements H302: Harmfulifswallowed.

H311: Toxicincontactwithskin.

H314: Causessevereskinburnsandeyedamage.

H317: Maycauseanallergicskinreaction.

H331: Toxicifinhaled.

H410: Verytoxictoaquaticlifewithlonglastingeffects

Precautionary statements P261: Avoidbreathingdust.

P273: Avoidreleasetotheenvironment.

P280: Wearprotective gloves/protective clothing/ eye protection/

face protection.

P305 IF IN EYES: Rinse cautiously with water for several minutes.



NO.813 SELF TRADE BUILDING F.T.Z. DALIAN CHINA

+P351: Remove contact lenses, if present and easy to do. Continue

+P338: rinsing.

P310: Immediately call a POISON CENTER or doctor/physician. P501: Dispose of contents/container to an approved waste disposal

plant

Supplemental Hazard Statements None.

Section 3 Composition/information on ingredients

Chemical characterization Pures

Component

| 26530-20-1 | 2-n-Octyl-4-isothiazolin-3-one | ≥98% |
|------------|--------------------------------|-------------|
| 7732-18-5 | 7732-18-5 Water | ≦ 2% |

^{*}All concentrations are percent by weight.

Section 4 First-aid measures

Description of first aid measures

Inhalation Move subject to fresh air.

Eye Contact Immediately flush eyes with a large amount of water for at least

15minutes. Get prompt medical attention.

Skin Contact Wash affected skin areas thoroughly with soap and water immediately

after exposure. Remove and wash contaminated clothing thoroughly. Do not take clothing home to be laundered. Discard contaminated shoes, belts and

other articles made of leather. Get prompt medical attention.

Ingestion If swallowed, give 2 glasses of water to drink. Immediately see a physician.

Never give anything by mouth to an unconscious person.

Note to Physician Material is corrosive. It may not be advisable to induce vomiting. Possible

mucosal damage may contraindicate the use of gastric lavage.

Indication of any immediate medical attention and special treatment needed: No date available.

Section 5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents Water spray jet, extinguishing powder, CO2, foam.

Special hazards arising from Nitrogen oxides (NOx), Carbon oxide(CO), Sulphur oxides.

The substance or mixture

Advice for firefighters Wear self-contained breathing apparatus and protective suit. Further information Cool containers/tanks with water spray. Minimize exposure.

Do not breathe fumes.

Section 6 Accidental release measures

Personal precautions, Wear respiratory protection. Avoid dust formation. Avoid breathing vapors, mistorgas. Ensuread equateventilation. Evacuate personnel to

And emergency procedures safe areas. Avoid breathing dust. Protective clothing, including

chemical splash goggles, nitrile or butyl rubber full length gloves,



NO.813 SELF TRADE BUILDING F.T.Z. DALIAN CHINA

rubber apron, or clothing made of nitrile or butyl rubber, and rubber overshoes must be worn during spill clean-ups and deactivation of this material. If material comes in contact with the skin during clean-up operations, immediately remove all contaminated clothing

and wash exposed skin areas with soap and water.

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not let product

enter drains. Discharge into the environment must be avoided.

Methods and material for Containment and cleaning up Pick up and arrange disposal without creating dust, Sweep up and

shovel, Keep in suitable, closed containers for disposal.

See section13 for further information.

Section 7 Handling and storage

Precautions for safe handling Avoid contact with skin and eyes. Avoid inhalation of vapour or

Conditions for safe storage,

The maximum recommended storage temperature for this Including any incompatibilities material is 37oC/131F.The minimum recommended storage

temperature for this material is 1°C/32F. Store in cool place. Keep

container tightly closed in a dry and well-ventilated place.

Containers which are opened must be carefully resealed and kept

upright to prevent leakage.

Specific end uses No data available.

Section 8 Exposurecontrols/personal/protection

Control parameters parameters Components with workplace control

Avoid contact with skin, eyes and clothing. Wash hands before **Engineering Controls**

> breaks and immediately after handling the product. Use local exhaust ventilation with a minimum capture velocity of 150ft/min.

(0.75m/sec.) at the point of dust or mist evolution. Refer to the

current

edition of Industrial Ventilation: A Manual of Recommended Practice published by the American Conference of Governmental Industrial Hygienists for information on the design, installation,

use, and maintenance of exhaust systems.

Personal protective equipment

Eye/face protection Face shield and safety glasses Use equipment for eye protection

tested and approved under appropriate government standards such

as NIOSH(US)orEN166(EU).

Skin protection Handle with gloves. Gloves must be inspected prior to use. Use

proper glove removal technique (without touching glove's outer

surface) to avoid skin contact with this product. Dispose of

contaminated gloves after use in accordance with applicable laws

and good laboratory practices. Wash and dry hands.



NO.813 SELF TRADE BUILDING F.T.Z. DALIAN CHINA

The gloves listed below provide protection against permeation:

Nitrile/ Butylrubber.

The selected protective gloves have to satisfy the specifications of

EU Directive89/686/EEC and the standard EN 374derived from it

Body Protection Complete suit protecting against chemicals. The type of

protective equipment must be selected according to the

concentration and amount of the dangerous substance at the

specific workplace.

Respiratory protection Where risk assessment shows air-purifying respirators are

appropriate use a full-face particle respirator type N100 (US) or

type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators

and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Other protective equipment Facilities storing or utilizing this material should be equipped

with an eyewash facility and a safety shower.

Section 9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

a) Appearance: b)Odor: Odorless c) Odour threshold: No data available

Form: Liquid d)pH-value: 4.0-7.0 e)Melting point:18° C

Color: Yellow (1%water solution)

f) Boiling point/Boiling range: 120° C/0.01mmHg

g) Flash point: Not applicable h) Evaporation rate: Not determined

i) Flammability (solid, liquid): Not applicable

j) Upper/lower flammability or explosive limits: Not applicable

k) Vapor pressure: Not applicable 1) Vapour density: Not applicable

m) densityat20° C: 1.03-1.05g/cm3 n)Water solubility: <0.1g/100mLat19° C

o) Partition coefficient(Kow): Not Determined p)Autoignition temperature: Not applicable

q) Decomposition temperature: Not Determined r) Viscosity: Not Determined

s) Explosive properties: No an explosionhazard

• Other information: No further relevant information available.

Section 10 Stability and reactivity

Reactivity No data available

Instability This material is considered stable under specified conditions of

storage, shipment and/or use. Seesection 7, Handling and

storage, for specified conditions.

Possibility of hazardous reactions

No dangerous reactions known.

Thermal decomposition/ Conditions to be avoided



NO.813 SELF TRADE BUILDING F.T.Z. DALIAN CHINA

Incompatibility Avoid contact with the following:

oxidizing agents, reducing agents, amines, mercaptans.

Hazardous decomposition products Thermal decomposition may yield the following:

oxides of nitrogen, sulfur dioxides.

Section 11 Toxicological information

Acute oral toxicity LD50,Rat: 760mg/kg

Acute inhalation toxicity Rat,4h: 0.33mg/L Active ingredient

Acute dermal toxicity

Skin irritation

Eye irritation

LD50,Rabbit: 690mg/kg

Rabbit, Corrosive (product)

Rabbit, Corrosive(product)

Serious eye damage/eye irritation Eyes-rabbit-Severe eye irritation Respiratory or skin sensitization May cause allergic skin reaction.

Carcinogenicity Non-carcinogenicity. No component of this product present

at levels greater than or equal to 0.1% is identified as

probable, possible or confirmed human carcinogen by IARC.

Mutagenicity Collective data indicate non-mutagenic.

Teratogenicity Not teratogenic.
Sensitization Skin sensitizer.
Reproductive toxicity Not teratogenic.
Specific target organ toxicity No data available

-single exposure

Specific target organ toxicity

No data available

-repeated exposure

Inhalation May cause respiratory irritation.

Aspiration hazard No data available

Potential health effects

Inhalation Toxic if inhaled. Material is extremely destructive to the

tissue of the mucous membranes and upper respiratory tract.

Ingestion Harmful if swallowed.

Skin May be harmful if absorbed through skin. Causes skin burns.

Eves Causes burns.

Signs and Symptoms of Exposure To the best of our knowledge, the chemical, physical, and

toxicological properties have not been thoroughly

investigated.

Section 12 Ecological informations

Elimination information (persistence and degradability)

Physico-chemical removability Activated Sludge Respiration Inhibition EC50: 47mg/L ai

Ecotoxicity effects

Toxicity to fish LC50 Oncorhynchus mykiss (rainbow trout) 96 h 0.047 mg/L

Active ingredient

Toxicity to fish LC50 Bluegill sunfish 96 h 0.18mg/L Active ingredient



NO.813 SELF TRADE BUILDING F.T.Z. DALIAN CHINA

Toxicity to algae EC50 Algae (Selenastrum capricornutum) 0.004mg/L Active

ingredient

Toxicity to aquatic invertebrates

Ozone depletion potential

Photochemical ozone creation

potential

EC50 Daphnia magna 48 h 0.32 mg/L Active ingredient

No report proves the ozone depletion potential

No report proves the Photochemical ozone creation potential

Section 13 Disposal considerations

Methods of disposal When a decision is made to discard this material as supplied, it is

classified as a RCRA hazardous waste with the characteristic of corrosive .Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations (See 40 CFR 268). Offer surplus and non-recyclable solutions to a licensed disposal

company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped

with an afterburner and scrubber.

Contaminated packaging Dispose of as unused product.

Section 14 Transport information

DOT

Proper shipping name Corrosive, liquid, toxic, n.o.s.(2-n-Octyl-4-isothiazolin-3-one)

UN-Number UN2922 Class 8/6.1 Packing group II

IMO/IMDG

Proper shipping name Corrosive, liquid, toxic, n.o.s. (2-n-Octyl-4-isothiazolin-3-one)

UN-Number UN2922 Class 8/6.1 Packing group II

IATA-DGR

Proper shipping name Corrosive, liquid, toxic, n.o.s. (2-n-Octyl-4-isothiazolin-3-one)

UN-Number UN2922 Class 8/6.1 Packing group II

Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations.

Section 15 Regulatory information

The product is classified and labelled according to Regulation (EC) No1272/2008 [EU-GHS/CLP] and European Directive 67/548/EEC as amended.

Labelling according Regulation (EC)No1272/2008[CLP]

Hazard pictograms









NO.813 SELF TRADE BUILDING F.T.Z. DALIAN CHINA

Signal word Danger Hazard statements H302: Harmful if swallowed. H311: Toxic in contact with skin. H314: Causes severe skin burns and eye damage. H317: May cause anallergicskinreaction. H331: Toxic if inhaled. H410: Very toxic to aquatic life with long lasting effects. Precautionary statements P261: Avoid breathing dust. P273: Avoid release to the environment. P280: Wear protective gloves/protective clothing/ eye protection/face protection. P305 IF IN EYES: Rinse cautiously with water for several minutes. +P351: Remove contact lenses, if present and easy to do. Continue +P338: rinsing. P310: Immediately call a POISON CENTER or doctor/physician. P501: Dispose of contents/container to an approved waste disposal

Supplemental Hazard Statements None.

For professional users only.

China. Inventory of Existing Chemical Substances (IECSC): All intentional components are listed on the inventory, are exempt, or are supplier certified.

plant

US. Toxic Substances Control Act(TSCA): All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

European Union: The European classification of the product is based on the results of toxicity and/or ecotoxicity tests and not the calculation method (Directive 99/45/EEC)

Section 16 Other information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Abbreviations and acronyms

| | y y | |
|-------|---|--|
| CAS | Chemical Abstracts Service (Registry Number) | |
| NIOSH | National Institute for Occupational Safety and Health | |
| OSHA | Occupational Safety and Health Administration | |
| LC50 | LC stands for lethal concentration. LC50 is the concentration of a material in air which causes the death of 50% (one half) of a group of | |
| | test animals | |
| LD50 | LD stands for Lethal Dose. LD50 is the amount of a material, given all at once, which causes the death of 50% (one half) of a group of | |

test animals.

^{*}Data compared to the previous version altered.