# GeofanTex WNs Range

### **Technical Data Sheet**

#### GeofanTex WNs Jan. 2018

GeofanTex WNs (Polypropylene woven geotextile) is made of polypropylene filaments using the latest in woven technology. PP offers excellent resistance to extreme pH conditions in groundwater and microbiological attack. Our PP woven geotextiles offer exceptionally high tensile strength from comparatively low amounts of raw material. This enables these products to offer extremely cost effective reinforcement. Such products are typically used for:

- ground stabilisation works
- temporary structures and working platforms

#### **Mechanical Properties**



Item	Unit	Unit Specifications								
		WNs	WNs	WNs	WNs	WNs	WNs	WNs	Nista	
		015	022	028	035 04	042	056	070	Note	
Tensile Strength MD [ASTM D 4595]	KN/m >=	20	30	40	50	60	80	100		
CD Tensile Strength [ASTM D 4595]	KN/m >=	15	22	28	35	42	56	70		
Tensile Elongation [ASTM D 4595]	%< =				25				MD/CD Average	
Widths windage	%				-1.0					
CBR Puncture Resistance [ASTM D 6241]	KN>=	1.6	2.4	3.2	4.0	4.8	6.0	7.5		
Pore Size O <sub>90</sub> (O <sub>95</sub> ) [ASTM D 4751]	mm	0.08-0.5								
Vertical Permeability [ASTM D 4491]	cm/s			к	x (10 <sup>-1</sup> -10 <sup>-3</sup> )				K=1.0-99	
UV Resistance Strength retention [ASTM D 4355]	% > =				70(500h)					
Tear Strength [ASTM D 4533]	KN>=	0.3	0.45	0.5	0.6	0.75	1.0	1.2	MD/CD Average	
Physical Identification Pr	operties									
Mass per unit area	g/m²	120	160	200	240	280	340	400		
warp	%				± 10					
Roll Width	m(≥)	5.95	5.95	5.95	5.95	5.95	5.95	5.95		
Approx. Loading Q'ty Per 40' HQ	Sqmts	193,375	156,190	115,280	100,405	92,970	70,655	59,500		

Above values are on an average basis, the data was obtained from in-house test laboratory, National test institutes and international test institutes. Geofantex Geosynthetics keeps the right of data changes and the final explanation right. Liability Exclusion: This publication should not be construed as engineering advice. While information contained here is accurate to the best of our knowledge, Geofantex Geosynthetics does not warrant its accuracy or completeness. The only warranty made by Geofantex Geosynthetics for its products is set forth in our Product Test Report accurage iour singulation of the products, or such other written warranty as may be greed by Geofantex Geosynthetics and customer. Geofantex Geosynthetics specifically disclaims all other warranties express or implied, including without agreed by Geofantex Geosynthetics specifically disclaims all other warranties, express or implied, including without agreed by Geofantex Goosynthetics and customer. Geofantex Geosynthetics and customer is accurate or customer. Geofantex Geosynthetics and customer is accurated as the second of the second of



## Geofantex Geosynthetics Co., Ltd.

201 Yiyilou, 100 Wenhua Street , Zhongshan Dist., Dalian, China TEL.:86-411-39569550 Fax: 86-4008266163-44899 Web:<u>www.geofantex.com</u> Email:info@geofantex.com