HIGOLD

PDLS Series Seasoning Pull Out Basket

Installation manual

Please note before installation

The PDLS series seasoning pull out basket is available for cabinets with a minimum depth of 500mm and a minimum installation height of 800mm. The width should be selected according to the cabinet width. Please pay attention to the cabinet size during installation.

PDLS 2-Series Seasoning Pull Out Basket

List of accessories

Installation accessories/materials are listed in the table below. Check if all listed standard cabinet parts are in stock.

Fastening Pull Out Basket Body x 5 Pcs/Set

Door Fixing PC Brackets + Short P

Divider + Long PC Metal Bracket *2

2 pcs M4*8 screws (spare, pre-installed plastic insertions), 20 pcs ST4.2*16 self-tapping screws

Installation template (including cut-out installation template and door panel installation template) *1

Installation of slide rails

Before installing the slide rails, fold the installation template along the dotted line firstly.

When fixing the installation template, the left edge is with the front edge and side edge of the cabinet, then use a carpenter's pencil to mark the positions of the slide rail fixing holes (left/right).

Align the slide rail holes with the marked points, and secure the slide rails (left/right) using ST4.2*16 self-tapping screws. To ensure the bearing capacity and stability of the slide rails, at least 3 self-tapping screws should be used to fix each side of the rail.

Slide rail installation completed.

Seasoning Pull Out Basket Body Installation

Place the seasoning basket body on the rail and push it in to position.

Pull out the baffle plate of the drawer body, snap into the rear grooves of the basket body (left/right).

Note: The rail cabinet sleeve can be rotated, adjusted according to the customer's degree between the tailstock of the guide rail and the groove of the basket. If it is not right enough to fill into the groove of the basket, the tailstock hook rubber sleeve can be removed.

Adjust the front adjustable tabs of the basket body to align with the front holes of the slide rails.

Locking and fixing of the basket with 2 pcs M4*8 screws (pre-installed screws) in the front and rear (left/right).

The installation and fixation of the basket body are completed.

Door Panel Installation

Find the two pre-drilling holes on the basket frame corner pieces and adjust the left and right positions of the door panel fixing plate so that the door panels are aligned on both sides.

Use a standard cabinet door panel. Align the positions of the door panel fixing holes with the pre-drilled holes at the bottom edge of the door panel, and mark the positions of the fixing holes (left/right) with a carpenter's pencil.

Pre-drill the door panel fixing parts. Align the mounting holes of the door panel fixing parts with the marked points on the door panel, and fix them with 4 pcs ST4.2*16 self-tapping screws in total (left/right).

After adjusting the left and right positions of the door panel fixing lock, the four self-tapping screws in the installation hole and two ST4.2*16 self-tapping screws in the middle of the door panel fixing lock for locking.

Remove the rail bottle rack to facilitate the installation of the door panel. Lift it up and remove it from the bottom.

Reinstall the door panel into the cabinet body.

Adjust the 4 pcs pre-installed screws on the corner pieces allows for adjustment of the door panel's front-and-rear angle (left/right).

Adjust the top and bottom of the door panel to be flush with the cabinet (left/right).

After the door panel installation is tightly and evenly with the cabinet, tighten the 4 pcs screws in the corner holes to fix the door panel (left/right).

The door panel installation is completed.

Accessories Installation

Reinstall the rail bottle shelf onto place metal dividers on both sides by clamping them tightly.

Align metal dividers to snap into the short dividers on fixing brackets.

The installation of the PDLS Series Seasoning Pull Out Basket is completed.

HIGOLD