

PLUNGER TYPE CYLINDER



Features:

- Mainly used for Snow Plow.
- Working pressure: 3000PSI.
- Pin holes at base and rod end.
- Two 1/4" ports 90 degrees apart or inline.
- Can be made as required.
- Both single acting or Double acting available.
- Interchangeable with most famous Plow brand.
- Ideal choice for good price and reliable quality.

MODEL	REPLACEMENT	STROKE	INSIDE DIAMETER	OUTSIDE DIAMETER	ROD DIAMETER	PORT	WEIGHT (LBS)
SPA15100750	ARCTIC	10.00"	1.75"	2.00"	1.5"	1/4-NPT	12
SPA15120750	ARCTIC	12.00"	1.75"	2.00"	1.5"	1/4-NPT	13
SPF15101000	FISHER	10.00"	1.75"	2.00"	1.5"	1/4-NPT	11
SPF15121000	FISHER	12.00"	1.75"	2.00"	1.5"	1/4-NPT	13
SPF20161250	FISHER	16.00"	2.25"	2.50"	2.00"	1/4-NPT	27
SPM15060625	MEYER	6.00 "	1.75"	2.00"	1.5"	1/4-NPT	9
SPM15100625	MEYER	10.00"	1.75"	2.00"	1.5"	1/4-NPT	14
SPM15120625	MEYER	12.00"	1.75"	2.00"	1.5"	1/4-NPT	15
SPM20120625	MEYER	12.00"	2.25"	2.50"	2.00"	1/4-NPT	24
SPW15060750	WESTERN	6.00 "	1.75"	2.00"	1.5"	1/4-NPT	11
SPW15080750	WESTERN	8.00"	1.75"	2.00"	1.5"	1/4-NPT	12
SPW15100750	WESTERN	10.00"	1.75"	2.00"	1.5"	1/4-NPT	14
SPW15101000	WESTERN	10.00"	1.75"	2.00"	1.5"	1/4-NPT	14
SPW20060750	WESTERN	6.00 "	2.25"	2.50"	2.00"	1/4-NPT	18
SPW20101000	WESTERN	10.00"	2.25"	2.50"	2.00"	1/4-NPT	22
SPW20161000	WESTERN	16.00"	2.25"	2.50"	2.00"	1/4-NPT	31

●Other brand and special made are available.