

Flow Scale LCS-60T

i. Applications

Used for accumulating volume in the area of the grain processing, chemical, grain depot, port etc

ii. Technical Parameters

| | |
|--------------------------|-------------------------------|
| Model | LCS-60T |
| Capacity(T/h) | 60 |
| Accuracy Grade | X(0.2) |
| Power, Power Consumption | AC 220V 50Hz 70W |
| Air, air expenditure | 0.4~0.6MPa 1m ³ /h |
| Outside height (mm) | 2750 |

iii. Main Configuration

| Name | Brand |
|---------------------|-------------------|
| Weighing controller | China / Zhiyuanda |
| Power switch | Taiwan/Mingwei |
| Button、 knob | France/ Schneider |
| Load cell | China /ZEMIC |
| Pneumatic element | Taiwan/airtac |
| Cylinder | Taiwan/AirTac |
| Solenoid valve | Taiwan/airtac |

iv. Functions and Features

- Fully sealed design of streamlined host and electric control box (no dust)
- The feeding and measuring mechanism adopts wear-resistant imported stainless steel material, which has a long service life.
- The machine control unity is neat and smooth.
- RS232 / 485 serial port is reserved for data communication with peripheral management

system.

- Optional printer can print out production output and other information.

v. Photo

