

DKJL

Aluminum Wire Double clipper 机械铝丝双卡打卡机系列



- DKJLK4打卡速度1-9级可调，单机可达100time/min。
- 采用铝盘丝封口，打卡后扣形美观，成扣为鸡心形。
- 可打肠衣折径范围25~160mm。K1~K4模具，可自由更换。
- 全机型设有自动润滑，加油次数可调，可设定整机自动润滑，自动加油系统。
- 具备自动裁断功能，0~9支任意选择。
- 拉伸距离45~100mm有级调整，能满足产品不同饱满程度的要求。
- 可与定量灌装机联机，实现自动化生产。
- 打卡中心高度920~1060mm，可调整。
- DKJLK2联机速度可达120根/分烤肠。

The clipping speed of DKJLK4 is adjustable, from 1~9 level. The maximum speed of single working is 100 times/min.

Using aluminum wire for clipping, the clip is nice and have heart shape.

Can use for sausage with Semi-perimeter: 25~160mm. K1~K4 mold change freely.

All model have automatic lubricate function, refuel time is adjustable.

Can set whole machine automatic lubricate and automatic refuel system.

With automatic cutting function, cutting amount is adjustable from 0~9.

Stretching distance is level adjustment from 45 to 100mm, can meet the request of different kind of sausage.

Can connected with vacuum filler, achieve automatic production.

The height of the clipping center is adjustable from 920~1060mm.

DKJLK2 connected with vacuum filler, the production speed can achieve 120pcs/min.



■ DKJL K4II



■ DKJL K2

肠衣折径以尼龙复合膜为例 Casing semi-perimeter is as per nylon compound film

型号 Type	外形尺寸(mm) External Dimension	功率(kw) Power	电压(V) Voltage	适用卡型 Clips	适用肠衣折径(mm) Casing Semi-perimeter	模具型号 Mould model	载刀工作压力(MPa) Cutting Pressure	打卡速度 (time/min) Speed	拉伸距离(mm) Expansion	重量(kg) Weight
DKJLK4II	1862 × 1133 × 1680	3.5	三相380V 50HZ	铝盘丝	25-160	K1-K4	0.5-0.6	100	45-100	833
DKJLK2	1380 × 1250 × 1450	3.5	三相380V 50HZ	铝盘丝	25-80	K1 K2 50	0.5-0.6	120	30	427
DKJU200	1185×870×1950	0.2	单相220V 50HZ	U210、U220	45-135		0.5-0.7			143