

YSZ200/800 Saline Mixer 盐水制备机



- 盐水制备机采用不锈钢材质，设计美观，便于清洗。
- 高速旋转的混合头，不但能充分的混合物料，且具有剪切功能，可以把大颗粒剪切成微小颗粒，易于溶解。
- 大大避免注射机注射时，针头堵塞的问题。
- 提高工作效率，减轻工人劳动强度。
- Adopt stainless steel. Carefully designed. Easy to be cleaned up.
- Mixer head with high speed that can not only mix up the materials but also can cut big pieces into small granules that can be easily dissolved.
- To avoid needles jammed during the injection.
- To increase productivity and to reduce intensity of workers.



LC200III Meat wagon 料车

料车外型尺寸根据国际标准制造。
采用不锈钢板制造并进行表面处理，易清洗、经济耐用。
可与提升机配套使用。重量40±0.2(kg)

料车外形尺寸 LC200III: 764×714×683(mm)
LCGR600: 1600×910×900(mm)

料车清洗架外形尺寸:1270×760×1650(mm)

The external dimension is manufactured according to the international standards.

Adopted imported stainless steel plate to produce and the surface has been processed carefully. It is easy to be cleaned up. And it is economic and durable.

In combination with elevator as a system. Weight:40±0.2(kg)

External dimension LC200III : 764×714×683(mm)

LCGR600:1600×910×900(mm)

Cleaner for skip car External dimension: 1270×760×1650mm.



料车
Meat wagon

型号 Type	外形尺寸(mm) External Dimension	电压 Voltage	功率(kw) Power	料箱容积(L) Capacity	转速(rpm) Speed	重量(kg) Weight
YSZ200	660 × 1000 × 1200	3相380V 50HZ	1.5	200	2840	55.6
YSZ800	1330 × 1040 × 1410	3相380V 50HZ	7	800	1800	

CRYO Fresh 液氮速冻柜



- 采用世界顶尖液氮锁鲜核心技术
- 以-196° C超低温液氮作为冷源
- 通过强制对流方式实现快速冷冻口完整封存食材水分、营养与品质
- 响应灵活、能耗低、简单易操作
- 多规格适应不同食材及工艺
- Using the world's top liquid nitrogen lock fresh core technology
- Using -196 degree C ultra low temperature liquid nitrogen as cold source
- Through forced convection to achieve fast freezing mouth complete storage of food moisture, nutrition and quality
- Flexible response, low energy consumption and easy operation.
- Multiple specifications for different ingredients and techniques



< 安全可靠 >
多重安全互锁设计

确保操作人员和生产场所的安全可靠

卫生环保 >
严格遵循食品机械标准

食品级 SS304 不锈钢全焊接结构，整机和内件方便移动及清洗，完全符合卫生工程学设计

高配置 >
德国顶级品牌低温阀门
PLC自动控温

采用最新低温保温材料，友好的人机操作界面

< 低能耗 >
专利设计高效
冷量传送风扇

高效风曲迅速形成超低温风场，提高冷量利用效率，降低30%液氮能耗

< 响应灵活 >
人性化设计，
响应迅速及时

设备采用德国先进设计技术，操作简便；运动部件较少，便于维护；占地面积较小，可以充分提高空间利用率

配方模式 >
不同食材特性
定制锁鲜配方

16种保密锁鲜配方记忆，确保产品质量始终如一

型号 Type	外形尺寸(mm) External Dimension	电压 Voltage	制冷剂/供应压力 Refrigerant / supply pressure	温度控制范围 Temperature control range	制冷剂管接口 Refrigerant pipe interface	重量(kg) Weight
C50	940 × 1045 × 1320	220V AC 50Hz 4A L+N+PE	液氮/3-5 bar(g)	常温至-100 °C (特殊温度需提前告知)	ZG2"管螺纹连接	310
C500	1320 × 1140 × 1495	380V AC 50Hz 8A 3P+N+E			φ 150mm法兰连接	540
C2000	1585 × 1460 × 2035	380V AC 50Hz 10A 3P+N+E			φ 150mm法兰连接	1250
C3000	1900 × 1650 × 2235	380V AC 50Hz 10A 3P+N+E			φ 219mm法兰连接	1500