

JG/MD

JG Band Saw Machine 食品用锯骨机
MD Knife Sharpener 磨刀机



MDJ300绞肉机刀磨刀机 不锈钢工作台

均采用SUS304不锈钢加工而成。锯骨机用于骨头的切割。

MD200-E斩拌刀磨刀机主要用于对斩拌刀(ZB125、ZB200)的修磨、抛光,也可用于其它切割刀具(如:切刀、去骨刀、屠宰刀等)的修磨。

Adopted SUS304 stainless steel. Band Saw is used for bone cutting.

MD200-E Knife Sharpener is used for knife sharpening and polishing, especially for knife of Bowl cutter.



■ MD200-E斩拌刀磨刀机

■ JG 300食品用锯骨机

■ JG 260食品用锯骨机

Sharpener for bowl cutter knives

Band Saw

Band Saw

GCY12 SG2/5 Manual Filler 液压/手动灌肠机
ZSSD4/ZSSQ2 Manual Saline Injector 手动泵压/气压注射机
HHS9824 Manual Activator 手动活化机

手动灌肠机制造工艺: 纯不锈钢材铸造, 完全用手工抛光工艺制造而成。

手动盐水注射机: 能使调味材料和营养成分经注射渗入到肉块内部, 扩散均匀加工出的产品口感良好, 色泽均匀诱人。

手动活化机: 将无骨肉挤入相对转辊之间的缝隙。正反转得到压实效果, 使肉的组织结构变得松软。

Manual filler manufacturing craft: made of stainless steel, totally manually polished.

Manual saline injector: injected the flavoring and nutrition into the meat, even infiltration produced good taste and attractive color.

Manual activator: put the meat into the gap of the shafts. Softened the meat structure.



■ GCY12液压灌肠机

■ SG5手摇式灌肠机

■ SG2手压式灌肠机

■ 手动泵压注射机

■ 手动气压注射机

■ HHS9824手动活化机

Hydraulic sausage filer

Hand Filler

Hand Filler

Manual Pump Press Injector

Manual Air Press Injector

Manual Tenderizer

型号 Type	外形尺寸(mm) External dimension	电压 Voltage	功率(kw) Power	转速(rpm) Rotation speed	锯条速度(m/s) Saw blade velocity	重量(kg) Weight
JG250	510 × 500 × 887	单相220V 50HZ	0.75	750	7.85	50.5
JG260	690 × 550 × 1500	单相220V 50HZ	1.1	1490	20.4	110
JG300	1662 × 940 × 836	3相380V 50HZ	2.2	1490	23.4	197
JG300A	910 × 700 × 1575	3相380V 50HZ	2.2	1490	23.4	150
MD200-E (磨斩拌机刀) For Bowl cutter	800 × 1000 × 500	3相380V 50HZ	1.2	砂轮转速400rpm	抛光轮转速1500rpm	125
MDJ300 (磨绞肉机刀) For Grinder	890 × 600 × 1300	3相380V 50HZ	1.5	砂轮转速1400rpm	/	125

型号 Type	外形尺寸(mm) External dimension	容积(L) Volume	压力(pressure) Weight	重量(kg) Weight	其它 Others
SG5	450×420×650	5	/	11.95	灌肠管直径为40mm/30mm/20mm/10mm Sausage Diameter
SG2	430×137×610	2	/	6	灌肠管直径为30mm/20mm/10mm Sausage Diameter
GCY12(液压)	680×440×1200	12	/	110	灌肠管直径为30mm/19mm/28mm Sausage Diameter
ZSSD4	835×650×800	10.5	0.4	72	电压: 2相220V 0.75KW Voltage: 2phase 220V 0.75KW
ZSSQ2	直径220 × 950	15	0.4	17.3	注射针长度170mm, 数量为2根、4孔/根 × 2套 Length of needle 170mm, two needles 4holes/piece × 2
HHS9824	450×220×300	/	/	17.5	注射针长度170mm, 数量为2根、4孔/根 Length of needle, two needles 4holes/piece