

TS200

TS200 LIFTER 提升机系列



■ 移动提升机架子
Frame of Movable Lifter ■ TY200Z

- 该机能平稳地将200L标准料斗车提升到指定位置，并将料斗车内物料倾倒在指定设备内，减轻劳动强度，提高劳动生产率。
- 采用不锈钢材质。
- 运行平稳、安全可靠、易于清洁、操作方便。采用进口双行程开关控制。
- 安装方式：固定式、移动式。
- The machine can raise a 200L standard hopper to designated position, and pour the material into appointed equipment.
- Reduce labor intensity and increase productivity.
- Whole machine adopts stainless steel material, with chain type and screw type.
- Run smoothly and safely, easy to clean and operate; Adopt the imported double stroke on-off control.
- Installation: fixing on the ground or movable.



■ T200 ■ 提升机配JR200绞肉机
Lifter Matched with Grinder JR200

型号 Type	外形尺寸(mm) External Dimension	电压 Voltage	功率(kw) Power	提升能力(kg) Capacity	提升速度(m/min) Speed	提升高度(mm) Height	重量(kg) Weight
TS200III	1520 × 1192 × 2945	3相380V 50HZ	1.1	250	3	1900	360
GRSLY1550II	1365 × 1275 × 1440	3相380V 50HZ	1.5	200	4.5	1550	325
GRSLQ1550II	1380 × 1000 × 1405	2相220V 50HZ	气压0.4-0.8Mpa perssure 1.5	200	3	1550	300
GRSLY945II	1230 × 1330 × 1400	3相380V 50HZ	1.5	200	4.5	945	305
GRSLQ1455	1000 × 895 × 1290	/	气压0.4-0.8Mpa perssure	200	3	1455	150
SLD500	3200 × 850 × 2300 (可定制)	3相380V 50HZ	1.1	提升距离(3000mm) Lifting hight	17.5	1650(可定制) can be made as per order	600

GRSL

GRSL Hydraulic Loading Machine 液压提升上料机

- 本机装有两组液压缸，可先将料车水平提升到目标高度，再进行翻转卸料，可适用于各种稀料、稠料、块料，提升过程中不漏料。
- 整机采用不锈钢材质，干净卫生，易于清洗，操作简单，运行平稳可靠。
- 一般用于滚揉机的上料。
- 可自由移动。可根据客户要求订制。
- There are two sets hydraulic cylinder installed in the machine, it can lift the skip car into a target height, not leaking any material during lifting, then overturn to discharge. Suitable for all kinds of materials, whether it is thick, thin, or blocks,
- The whole machine use stainless steel, clean and sanitary, easy to maintain and operation, machine function stable and reliable.
- Usually used for loading material for vacuum tumbler
- Move freely. Can be made as per order.



■ 两动液压提升机



■ 两动液压上料机
Hydraulic Two Actions Loader