

HIGH PRESSURE HYDRAULIC TOOLS

BMT-10 SERIES TOE JACKS

CAPACITY: 2T, 5T, 10T, 15T, 25T

FEATURES AND BENEFITS

- Complies with ANSI/ASME B30.1, CE/GS standards.
- Designed for lifting loads with very low minimum clearance (foot) or high clearance (head).
- Can be used in confined spaces.
- Built in safety valve for overload protection.
- Features spring assisted return and over travel protection on 5 and 10 ton models.
- Forged base and cylinder to assure strength.



| Model | Capacity | | Mini. Height | | Max. Height | | Weight |
|----------------|----------|-----|--------------|-----|-------------|-----|--------|
| | Toe | Top | Toe | Top | Toe | Top | |
| | ton | ton | mm | mm | mm | mm | kg |
| BMT-102 | 2 | 3 | 16 | 238 | 128 | 349 | 8 |
| BMT-105 | 5 | 6 | 22 | 298 | 141 | 409 | 24 |
| BMT-110 | 10 | 14 | 28 | 333 | 173 | 460 | 38 |
| BMT-115 | 15 | 30 | 32 | 345 | 185 | 500 | 48 |
| BMT-125 | 20 | 50 | 40 | 390 | 215 | 530 | 75 |

BMT-20 SERIES TOE JACKS

CAPACITY: 5T, 10T, 25T

FEATURES AND BENEFITS

- Complies with ANSI/ASME B30.1, CE/GS standards.
- Compact and stable construction.
- Housing revolves 360°.
- Lowering speed can be accurately adjusted.
- Safety valve for overload protection



| Model | Capacity | | Mini. Height | | Max. Height | | Weight |
|----------------|----------|-----|--------------|-----|-------------|-----|--------|
| | Toe | Top | Toe | Top | Toe | Top | |
| | ton | ton | mm | mm | mm | mm | kg |
| BMT-205 | 5 | - | 25 | 368 | 230 | 572 | 25 |
| BMT-210 | 10 | - | 30 | 420 | 260 | 650 | 35 |
| BMT-225 | 25 | - | 58 | 505 | 272 | 720 | 102 |