



BUTYL RUBBER SEALING TAPE

PRODUCT DESCRIPTION

JDHT BG-B butyl sealing tape is a self-adhesive tape, with PVDF, aluminum foil film or stich bonded fabric as cover, consists butyl rubber as adhesive layer, release liner on underside, which is applicable for various substrates.


CHARACTERISTICS / ADVANTAGES

- 1 Practical, various types available for different projects;
- 2 Easy to use, portable, cost saving, good pertinence;
- 3 Wide range of applications, such as home decorations, waterproofing maintenance, large scale waterproofing joints etc.

USES

- Detailing sealing
- Roofs
- Exterior walls
- Window frames
- Low pressure pipes maintenance

PRODUCT INFORMATION

Appearance / Color	black 
Shelf life	1 year
Thickness	1.0mm
Width	50mm,100mm,200m
Persistence,min ≥	20
Thermostability, 80℃, 2h	No flowing, cracks nor deformation
Flexibility at low temperature,-40℃	no cracks
Bonding strength under shear N/mm	
Membrane ≥	2.0
Peel strength N/mm	
Membrane ≥	0.4
Cement mortar board ≥	0.6
Colored steel ≥	0.6
Peel strength retention rate %	
Thermostability, 80℃, 168h	
Membrane,Cement mortar,Colored steel ≥	80
Alkali treatment, Saturated calcium hydroxide, 168h	
Membrane,Cement mortar,Colored steel ≥	80
Soaking, 168h	
Membrane,Cement mortar,Colored steel ≥	80