



Sinoscope

- 0° 4MM x 175MM
- 0° 4MM x 175MM Wide angle
- 30° 4MM x 175MM
- 30° 4MM x 175MM Wide angle
- 45° 4MM x 175MM
- 70° 4MM x 175MM
- 0° 2.7MM x 175MM Wide angle
- 30° 2.7MM x 175MM Wide angle

Larynoscope

- 70° 6MM x 175MM
- 70° 8MM x 175MM
- 90° 8MM x 175MM



Coupler

F16, F18, F20, F22, F25, F28, F32, F35



Otoscope

- 0° 4MM x 50MM
- 30° 4MM x 50MM
- 0° 4MM x 100MM
- 0° 2.7MM x 100MM
- 30° 2.7MM x 100MM

Laparoscope

- 0° 5MM x 330MM
- 30° 5MM x 330MM
- 0° 10MM x 330MM
- 30° 10MM x 330MM



Zoom Adaptor

F20-F35

Light Guide Cable autoclavable

JG-001041 4MM x 2500MM



Monitor

- LED 24"
- Resolution: 1980 x 1200
- Brightness: 450cd/m²
- Contrast ratio: 1000:1
- Visual angle: 178° (H) / 178° (V)
- Format: 16:10
- Video input: DVI-I, VGA, CVBS, S-VIDEO, YPbPr, RGBS, SDI
- Video output: DVI-I, CVBS, S-VIDEO, YPbPr, RGBS, SDI
- Size: 572mm x 469mm x 211mm
- Weight: 10.85kg



Trolley

- Layers and layer height adjustable, Proposal load ≤20kg/Layer
- Cart Size: 664mm x 638mm x 1650mm
- Worksurface height: 1125mm
- Worksurface Size: 527mm x 420mm
- Rocker arm for display, height - adjustable, 360° rotation for LCD, Standard Load ≤10kg, optional maxium load ≤21kg
- Special power wiring slot