

PANEL DIRECTIONAL ANTENNA

IP0727-0965

Features:

- Wide band design, 698~960/1710~2700MHz
- Simple installation & stable performance
- Good anti-vibration and aging resistance
- Small size and light weight
- Indoor wall mounting




Specification:

Frequency	698~960/1710~2700MHz
Bandwidth	262/990MHz
Gain	7~9dBi
VSWR	≤ 1.5
Max. power	100W
Impedance	50Ω
Polarization	Vertical
Horizontal Beamwidth	65°
Vertical Beamwidth	55°
Front to Back Ratio	≥ 18dB
PIM3	≤ -120dBc
Rated Wind Velocity	60m/s
Lightning Protection	DC Ground
Weight	≤ 0.9kg
Color	White
Operating Temperature	-10°C~+55°C
Dimension	210×180×43mm
Connector Type	N-Female or customized
Terminal line	White 5D-FB, L=350mm
Radiating Element Material	Aluminum Alloy
Radome Material	UV-Resistance ABS
Accessories for installation	Wall mounting

The Picture mentioned above is for reference only, and subjects to Amplitec's final confirmation.





Website: www.amplitec.net

Add: 4 Floor, 4 Building, No. 60 of the Langbao West Road, Chancheng District FoshanCity, Guangdong Province, China. 528000 Fax: (86)757-83123923 Tel: (86)757-83308393/83308238/83328273

Email: info@amplitec.cn

