

CAVITY POWER SPLITTER SP0727-XNB

Features:

- Wide Frequency Band
- Low Insertion Loss
- Low VSWR
- High Isolation
- Low PIM



Specifications:

Model:	SP0727-2NB	SP0727-3NB	SP0727-4NB
Frequency Band (MHz)	698 ~ 2700	698 ~ 2700	698 ~ 2700
Input Port	1	1	1
Output Ports	2	3	4
Split Loss(dB)	≤ 3.1	≤ 5.1	≤ 6.3
Insertion Loss (dB)	≤ 0.3	≤ 0.45	≤ 0.55
VSWR	≤ 1.25	≤ 1.25	≤ 1.25
PIM (dBc) @2*43dBm	≤ -120	≤ -120	≤ -120
Average Power(W)	300	300	300
RF Connector	3 x N-female	4 x N-female	5 x N-female
Working Temperature (°C)	-35~+65	-35~+65	-35~+65
Relative Humidity	5% ~ 95%	5% ~ 95%	5% ~ 95%
Impedance (Ω)	50	50	50
Cavity Material	Aluminum	Aluminum	Aluminum
Environmental Conditions	IP65	IP65	IP65
Color	Black-plated	Black-plated	Black-plated
Weight(kg)	≤ 0.4	≤ 0.45	≤ 0.5