

Optical Fiber Connectors&Adapters&Attenuators / 连接器&适配器&衰减器



Features 特点

PC, UPC, APC Multi Skive
Project
Low Insertion Loss
High Reliability And Stability

Applications 应用

Telecommunications System
High Return Loss Testing Equipment
CATV Systems
Long-haul Telecommunications
LAN System

Optical Specification 性能规范

Optical Fiber Connectors		Unit	FC/PC, FC/UPC, FC/APC, SC/PC, SC/UPC, SC/APC, ST/PC, ST/UPC, LC/PC, MU/PC, DIN, MT-RJ/PC				
			Single Mode			Multi-Mode	
			PC	UPC	APC	PC	UPC
Insertion Loss		dB	≤0.20	≤0.20	≤0.30	≤0.20	≤0.20
Return Loss		dB	≥45.00	≥50.00	≥60.00	≥38.00	≥42.00
Mechanical Performance (IL change)	Interconvertibility	dB	≤0.20				
	Variation	dB	≤0.20				
	Repeatability	dB	≤0.20				
Environmental Performance (IL change)	High Temperature	dB	≤0.20				
	Low Temperature	dB	≤0.20				
	Temperature Cycle	dB	≤0.20				
	Humidity	dB	≤0.20				

The above product information is for reference only, please contact our company for the latest information.



Adapters/Attenuators	Unit	On-line Optical Attenuator	Fixed Optical Attenuator
Wavelength	nm	1310/1550	1310/1550
Attenuation Value	dB	0-25	0-30
Attenuation Accuracy	dB	±3.00%	0-10±0.50%, 11-30±5.00%
Reflection Loss	dB	≥50.00(PC), ≥60.00(APC)	---