

C740



Features:

- 1.Supports SPP/BLE/HID mode;
- 2.Fast and accurate in reading 1D codes;
- 3.Large capacity battery, 1200mAh;
- 4.Long distance communication:
 - 2.4G Wireless: about 100m in open area;
 - bluetooth: about 10m in open area--can be customized to be 100m;
- 5.Large Storage: 2M, can store about 160,000 of EAN 13 barcodes;
- 6.SDK is available;
- 7.3 in 1 transfer function: Bluetooth+2.4G Wireless+ Wired USB ;

Applicable scope:

- Commercial POS system(Supermarkets)
- Warehousing and logistics
- Libraries
- Banks and Telecom
- Transportation
- Postal service
- Industrial and manufacturing management

Feature	
Light Resource	CCD (Safe visible light)
CPU	32 bit high resolution
Supported Symbolgies	EAN-13, EAN-8, UPC A, UPC E, CODABAR (NW-7), Code 39, Code93, Interleaved 2 of 5, Standard 2 of 5, Matrix 2 of 5, Code 128 EAN/UCC 128, Code 11
Charging Time	3~4hour
Scans Per Charge	30000 times
Precision	≥ 4mil (0.10mm)
Decode Speed	260 times/second
Decode Error Rate	Less than 1/8 million
Depth of Scan Field	Code 39 70mm~190mm(5mil) Ean-13 50mm~450mm(13mil) Code128 45mm~430mm(10mil)
Print Contrast Signal	≥ 20%
Scan Angle	Yaw(Skew)45° & Pitch60°
Working Distance	2.4G Wireless: about 100m in open area; bluetooth: about 10m in open area;
Battery Capacity	1200MAH

Mechanical / Electrical

Working Voltage	DC 3.3V
Current	Maximum current :150mA Standby current: 45mA (RS232) Sleep current :54.0mA(USB)
Rated Power Consumption	0.33W

Environment

Operating Temperature	-20°C~45°C
Storage Temperature	-20°C~45°C
Humidity	5%-85%

Packing list

- Scanner × 1
- User's Guide × 1
- Cable × 1
- 2.4G USB Receiver × 1

Packing details

Scanner	Weight	105*50*25mm
	3*4.3*12cm	100g
Inner Box	1pcs/box, 3*5*13cm,0.21kg;	
Carton	60 pcs/ctn, 48*35*40cm, 13.1kg	

