

NT-1202
Wired 2D barcode scanner



Optional:



Features

1. 32 bit CPU
2. Fast and accurate in reading 2D codes
3. Multiple interface, support USB (standard), RS232 (optional)
4. Full quakeproof, waterproof, dustproof, antiknock design
5. IP67 Industrial Grade, drop lots of time from 7 high meters still work normally, work under water for more than 30 minutes
6. Comfortable button, service life of button up to 5million times

Applicable scope

- ✓ Commercial POS system(Supermarkets)
- ✓ Warehousing and logistics
- ✓ Libraries
- ✓ Banks and Telecom
- ✓ Transportation
- ✓ Postal service
- ✓ Industrial and manufacturing management

Specifications	
Type of illuminant	CMOS (light : red LED (625±10nm))
Supported interfaces	USB (standard), RS232 (optional)
Decode Capability	2D: PDF417、QR Code (QR1/2, Micro)、Data Matrix (ECC200, ECC000, 050, 080, 100, 140)、Chinese Sensible Code, etc 1D : Code128, UCC/EAN-128, AIM128, EAN-8, EAN-13, ISBN/ISSN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-14, Matrix 2 of 5, Industrial 25, Standard 25, Code39, Codabar, Code 93, Code 11, etc
Precision	≥5mil (0.127 mm)
Operation	Manual, Automatic
Depth of scan field	EAN13(13mul) 50mm -195mm Code39(5mil) 50mm -105mm FDF417(6.67mil) 35mm - 135mm Data Matrix(10mil) 35mm - 140mm QR Code(15mil) 30mm - 165mm
Decode speed	5 in/s(12.7 cm)
Decode error rate	Less than 1/8 million
Print Contrast Signal	≥20%
scan angle	Yaw(Skew)65° & Pitch60°
Industrial Grade	IP67, 7 meters Drop Test
Safety	Full quakeproof, waterproof, dustproof, antiknock-design and EMI Shielding

Packing list	
Scanner × 1	
Cable × 1	
User's Guide × 1	

Mechanical / Electrical	
Power voltage	DC 5V
Working current	Operation230mA; Idle 60mA
Scanner Material	ABS+PC, Flammeresistant material

Environmetal	
Operating humidity	5%-95%
Storage humidity	5%-95%
Operating temperature	-20°C-50°C
Storage temperature	-20°C-60°C
Certifications	CE, IP67, ROHS, FCC, EMC, RED, LVD

Certifications	