



W8-WIFI

1	Optical Properties	
1.1	Image Sensor:	CMOS
1.2	Resolution:	1MP(1280*800)
1.3	Light Source:	(Aimer) Red color LED (Ilumination) White color LED
1.4	Reading Mode:	Image scanning
	Precision:	1D ≥3mil
		2D ≥5mil
1.6	Print Contrast:	≥15%
2. 1	Operating Environment	
2.1.1	Usage Environment:	-10°C-50°C
2.1.2	Storage Temperature:	-20°C-70°C
2.1.3	Working Humidity:	5%-95% (No condensation)
2.1.4	Ambient Lighting:	40,000 lx
2. 2	Electrical Character	ristics
2.2.1	Operating Voltage:	DC5.0V±5%
2.2.2	Maximum Current:	395mA
2.2.3	Battery Capacity:	2000MAH
2.2.4	Charging Time:	5-7 hours
2.3	Communication Method	
2.3.1	Bluetooth:	Bluetooth 4.2
2.0.1	Bluetooth Mode:	Bluetooth HID、Bluetooth SPP、Bluetooth BLE
2.3.2	WIFI:	WLAN IEEE 802.11 b/g/n
2. 4	Secondary Development	
2.4.1	Bluetooth:	SPP、BLE development
2.4.2	WIFI:	TCP/UDP/MQTT/AWS-IoT
2.4	Transmission performance	
2.4.1	Transfer Method:	Bluetooth transmission
		WIFI transmission

1242		Bluetooth: visible distance in the open air ≤ 10 meters	
		WiFi: Communication is possible within WiFi range	
3	Decoding performance		
3.1	Field of View:	34° V x 30° H(vertical horizontal)	
3.2	Scan Performance: (scanning depth of field)	EAN-13:50mm-365mm(13mil) Code 39:40mm-165mm(5mil) Data Matrix:35mm-115mm(10mil) QR Code:35mm-145mm(15mil) PDF 417:45mm-115mm(6.67mil)	
3.3	Decoding Ability	2D PDF 417 Micro PDF 417 Data Matrix QR Code Micro QR Aztec MaxiCode Direct Part Mark	
		1D UPCA / UPC E EAN8 / EAN 13 Code 128 Code 39 Code 93 Code 32 Code 11 Codabar PlesseyMSI Interleaved 2 of 5 IATA2 of 5 Matrix2 of 5. Straight2 of 5 Pharmacode RSS-14 RSS-14 ExpandedRSS-14 Limited Composite Code -A Composite Code -B Composite Code -C	
4	Other Performance		
4.1	Prompt Method:	Buzzer LED indicator light	
4.2	Scan Mode:	Button trigger mode Continuous scan mode Auto sensing mode Other scan modes	
4.3	Charging/data Interface:	USB (B) /USB (A)	
5	Physical Properties		
5.1	Size:	L*W*H (mm): 165*65*90mm	
5.2	Cable:	1.2m	
5.3	Color:	Black	
5.4	Weight:	Scanner weight: 0.17kg	
6			
6.1	Waterproof and Dustproof Sealing Level:	IP54	
6.2	Earthquake Resistance	1 meter high free fall	
1 63 L	Related Certifications:	CE、FCC、ROHS, etc.	