

NT-M10
Wired CCD barcode scanner



Features

1. Factory direct sale, cheap price and stable scanning
2. Fast and accurate in reading 1D codes
3. Service life of button reaches up to 8 million times.
4. Comfortable button, service life of button up to 5million times

Feature	
Light Resource	C C D (Safe visible light)
Port/Interface	USB (standard), RS232 (optional)
Supported Symbolgies	EAN-8, EAN-13, Codabar, CODE11, CODE 39, CODE 93, CODE128, China Post, GS1-128, GS1 Limited, GS1 Omnidirectional, UPC-A, UPC-E, ISBN/ISSN, ISBT, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, MSI, Plessey, ITF14
Presidion	≥4 mil/0.127mm@PCS90%
Depth of scan field	Code 39:110mm-170mm(0.127mm 5mil) Code 39:100mm-450mm(0.5mm 20mil) Code 39:240mm-480mm(1.0mm 40mil) UPC/EAN 13:100mm-250mm(0.33mm 13mil)
Resolution	2500
Decode speed	300 times/ second
Decode Error Rate	less than 1/8 million
Print Contrast Signal	≥10°
Scan Angle	Yaw(Skew) 60° Pitch 60°

Mechanical / Electrical

Voltage	5VDC ±5%
Current	Maximum current :130mA

Environment

Operating temperature	0°C~+50°C
Storage temperature	20°C~70°C
Humidity	5%-95%
Certifications	CE, ROHS, FCC


Optional:



Applicable scope

- ✓ Commercial POS system(Supermarkets)
- ✓ Warehousing and logistics
- ✓ Libraries
- ✓ Banks and Telecom
- ✓ Transportation
- ✓ Postal service
- ✓ Industrial and manufacturing management

Packing list

scanner × 1	
User's guide × 1	
cable × 1	

Packing details

scanner	Weight	165*65*90mm
	1pc/box; 190mm × 115mm ×85mm; 260g	275g;
Inner Box	50 sets/ctn;15kg/ctn; 600mm×450mm×420mm	
Carton	10500pcs; 150ctns	
20FT Container	7500pcs; 150ctns	
	23800pcs; 325ctns	

Certifications

