

NT-M5
Wired 2D barcode scanner



Features

1. Factory direct sale, cheap price and stable scanning
2. Fast and accurate in reading 2D codes
3. Comfortable button, service life of button up to 8million times

Feature	
Light Resource	CMOS
CPU	32 bit high resolution
Supported Symbolgies	2D: PDF417、QR Code (QR1/2, Micro)、Data Matrix (ECC200, ECC000, 050, 080, 100, 140)、Chinese Sensible Code 1D : Code128, UCC/EAN-128, AIM128, EAN-8, EAN-13, ISBN/ISSN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-4, Matrix 2 of 5, Industrial 25, Standard 25, Code39, Codabar, Code 93, Code 11,
Precision	≥ 5 mil (0.10mm)
Decode error rate	Less than 1/8 million
Depth of scan field	Code 39 40mm~165mm(5mil) Ean-13 50mm~365mm(13mil) Data Matrix 35mm~115mm(10mil) QR Code 35mm-145mm (15mil) PDF 417 45mm-115mm(6.67mil)
Print Contrast Signal	≥ 25°
scan angle	Yaw(Skew)55° & Pitch55°
Mechanical / Electrical	
Working Voltage	5VDC±5%
Current	Maximum current :260mA
Environment	
Operating temperature	0°C~+50°C
Storage temperature	-20°C~+70°C
Humidity	5%-95%

Optional:



Applicable scope

- ✓ Comercial POS system(Supermarkets)
- ✓ Warehousing and logistics
- ✓ Libraries
- ✓ Banks and Telecom
- ✓ Transportaion
- ✓ Postal service
- ✓ Industrial and manufacturing management

Packing list

scanner × 1	
User's guide × 1	
cable × 1	

Packing details

	Weight	165*65*90mm
scanner	1pc/box; 190mm × 115mm × 85mm; 220g	235g;
Inner Box	50 sets/ctn;12kg/ctn; 600mm×450mm×420mm	
Carton	10500pcs; 150ctns	
20FT Container	7500pcs; 150ctns	
	23800pcs; 325ctns	

Certifications

