

NT-L8 Wireless 2D barcode scanner

Features

1. Factory direct sale, cheap price and stable scanning
2. Fast and accurate in reading 2D codes
3. Service life of button reaches up to 8 million times.
4. Large capacity battery, continuous work for 8-10 hours after fully charged
5. Dual mode: wired and wireless
6. Mini Receiver

Feature	
Light Resource	CMOS
CPU	32 bit high resolution
Supported Symbolgies	2D: PDF417、QR Code (QR1/2, Micro)、Data Matrix (ECC200, ECC000, 050, 080, 100, 140)、Chinese Sensible Code 1D : Code128, UCC/EAN-128, AIM128, EAN-8, EAN-13, ISBN/ISSN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-4, Matrix 2 of 5, Industrial 25, Standard 25, Code39, Codabar, Code 93, Code 11,
Charging time	2~3hour
Scans per charge	30000 times
Precision	≥ 5 mil (0.10mm)
Decode speed	5 in/s(12.7 cm)
Decode error rate	Less than 1/8 million
Depth of scan field	Code 39 40mm~165mm(5mil) Ean-13 50mm~365mm(13mil) Data Matrix 35mm~115mm(10mil) QR Code 35mm-145mm (15mil) PDF 417 45mm-115mm(6.67mil)
Print Contrast Signal	≥ 30°
scan angle	Yaw(Skew)45° & Pitch60°
Working Distance	Over 30meter
Battery capacity	2000MAH
Mechanical / Electrical	
Working Voltage	3.3 VDC ±5%
Current	working 230mA Standby: 3.4mA (RS232) , 54.0mA(USB)
Rated power consumption	186mW
Environment	
Operating temperature	-20°C-45°C
Storage temperature	-20°C-45°C
Humidity	5%-85%

Optional:

Applicable scope

- ✓ Comercial POS system(Supermarkets)
- ✓ Warehousing and logistics
- ✓ Libraries
- ✓ Banks and Telecom
- ✓ Transportaion
- ✓ Postal service
- ✓ Industrial and manufacturing management

Packing list

scanner × 1

User's guide × 1

cable × 1

Packing details

scanner	Weight	165*65*90mm
	1pc/box; 190mm × 115mm × 85mm; 220g	235g;
Inner Box	50 sets/ctn;12kg/ctn; 600mm×450mm×420mm	
Carton	10500pcs; 150ctns	
20FT Container	7500pcs; 150ctns	
	23800pcs; 325ctns	

Certifications

