

NT-2015
wired barcode scanner



Optional:



Features

1. Super decoding ability
2. Decoding rate: 120 times per second
3. Customer setting: Barcode setting mode, easy to operate
4. Full independent intellectual property right
5. Intelligent AGC control
6. Antiknock, full quakeproof design, withstand 2m drops
7. Comfortable button, service life of button up to 5million times

Applicable scope

- ✓ Comercial POS system(Supermarkets)
- ✓ Warehousing and logistics
- ✓ Libraries
- ✓ Banks and Telecom
- ✓ Transportaion
- ✓ Postal service
- ✓ Industrial and manufacturing management

Feature	
Light Resource	650nm laser(Safe visible light)
Port/Interface	USB (standard)
Supported Symbolologies	Code 39, Full ASCII, Code bar, Industrial 2 of 5, Interleave 2 of 5, Code 93, Code 128, Code 32, Standard Code 39, EAN 1 28, MSI, EAN 8&13, UPCA&E, Plessey, DataBar14, TELEPE
Presicion	≥4 mil
Depth of scan field	0-80cm
Operation	Manual
Decode speed	120times/ second
Light intensity	Daylight, 4000Lux
Decode Error Rate	less than 1/5 million
Print Contrast Signal	≥30°
Scan Angle	Yaw(Skew) 45° pitch 60°

Mechanical/ Electrical	
Voltage	5V
Current	Operation 68mA, Idle 48mA
Scanner Material	Eco-friendly, ABS

Environmetal	
Operation Tempereture	-20℃-45℃
Storage Temperature	-20℃-45℃
Humidity	5%-85%
Certifications	CE, IP67, ROHS, FCC , EMC , RED, LVD

Packing list	
scanner × 1	
User's guide × 1	
cable × 1	

Packing details		
scanner	Size(L*W*H)	170mm*100mm*70mm
	Weight	235g;
	Without Stand	With Stand
Inner Box	1pc/box; 190mm × 115mm ×85mm; 320g	1pc/box; 210mm × 130mm ×100mm; 520g
	Carton	50 sets/ctn; 33kg/ctn; 600mm×450mm×420 mm
20FT Container	10500pcs; 150ctns	11250pcs; 225ctns
	7500pcs; 150ctns	
40FT Container	23800pcs; 325ctns	25000pcs; 500ctns
	16250pcs; 325ctns	

Certifications		

