

F20
1D wired CCD barcode scanner



Features

1. Factory direct sale, cheap price and stable scanning.
2. Fast and accurate in reading 1D codes and screen 1D codes.
3. Service life of button reaches up to 8 million times.
4. Comfortable button, service life of button up to 5million times.


Applicable scope

- ✓ Comercial POS system(Supermarkets)
- ✓ Warehousing and logistics
- ✓ Libraries
- ✓ Banks and Telecom
- ✓ Transportaion
- ✓ Postal service
- ✓ Industrial and manufacturing management

Feature	
Light Resource	C C D (Safe visible light)
Port/Interface	USB (standard), RS232 (optional)
Supported Symbologies	EAN-8, EAN-13, Codabar, CODE11, CODE 39, CODE 93, CODE128, China Post, GS1-128, GS1 Limited, GS1 Omnidirectional, UPC-A, UPC-E, ISBN/ISSN, ISBT, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, MSI, Plessey, ITF14
Presicion	≥5 mil
Depth of scan field	Code 39:120mm-160mm(0.127mm 5mil) Code 39:110mm-400mm(0.5mm 20mil) Code 39:260mm-420mm(1.0mm 40mil) UPC/EAN 13:120mm-200mm(0.33mm 14mil)
Resolution	1500
Decode speed	200 times/ second
Decode Error Rate	less than 1/8 million
Print Contrast Signal	≥10°
Scan Angle	Yaw(Skew) 60° Pitch 60°

Mechanical/ Electrical	
Voltage	5VDC ±5%
Current	Maximum current :130mA

Environmetal	
Operating temperature	0°C~+50°C
Storage temperature	20°C~70°C
Humidity	5%-95%

Packing list	
scanner × 1	
User's guide × 1	
cable × 1	

Packing details		
scanner	Size(L*W*H)	170mm*100mm*70mm
	Weight	235g;
Without Stand		
Inner Box	1pc/box; 190mm × 115mm ×85mm; 320g	
	50 sets/ctn;33kg/ctn; 600mm×450mm×420 mm	
Carton	70 sets/ctn; 33kg/ctn; 880mm×450mm× 420mm	
	10500pcs; 150ctns	
20FT Container	7500pcs; 150ctns	
	23800pcs; 325ctns	
40FT Container	16250pcs; 325ctns	

Certifications		
		