

F1900
1D wireless CCD barcode scanner



Features


1. Factory direct sale, cheap price and stable scanning.
2. Fast and accurate in reading 1D codes and screen 1D codes.
3. Service life of button reaches up to 8 million times.
4. Comfortable button, service life of button up to 5million times.

Applicable scope

- ✓ Comercial POS system(Supermarkets)
- ✓ Warehousing and logistics
- ✓ Libraries
- ✓ Banks and Telecom
- ✓ Transportaion
- ✓ Postal service
- ✓ Industrial and manufacturing management

Feature	
Light Resource	C C D (Safe visible light)
Port/Interface	USB (standard), RS232 (optional)
Supported Symbologies	EAN-8, EAN-13, Codabar, CODE11, CODE 39, CODE 93, CODE128, China Post, GS1-128, GS1 Limited, GS1 Omnidirectional, UPC-A, UPC-E, ISBN/ISSN, ISBT, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, MSI, Plessey, ITF14
Presicion	≥5 mil
Depth of scan field	Code 39:120mm-160mm(0.127mm 5mil) Code 39:110mm-400mm(0.5mm 20mil) Code 39:260mm-420mm(1.0mm 40mil) UPC/EAN 13:120mm-200mm(0.33mm 14mil)
Resolution	1500
Decode speed	200 times/ second
Battery capacity	2000MAH
Charging time	4~6 hours
Decode Error Rate	less than 1/8 million
Print Contrast Signal	≥10°
Scan Angle	Yaw(Skew) 60° Pitch 60°
Mechanical/ Electrical	
Working Voltage	DC 3.3V±5%
Current	Maximum current :265mA
Environmetal	
Operating temperature	0°C~+50°C
Storage temperature	20°C~+70°C
Humidity	5%-95%

Packing list

scanner × 1	
User's guide × 1	
cable × 1	

Packing details

scanner	Size(L*W*H)	170mm*100mm*70mm
	Weight	235g;
	Without Stand	
Inner Box	1pc/box; 190mm × 115mm ×85mm; 320g	
Carton	50 sets/ctn;33kg/ctn; 600mm×450mm×420 mm	
	70 sets/ctn; 33kg/ctn; 880mm×450mm× 420mm	
20FT Container	10500pcs; 150ctns	
	7500pcs; 150ctns	
40FT Container	23800pcs; 325ctns	
	16250pcs; 325ctns	

Certifications

