


D-8600



| | | |
|-------------------------------|--|--|
| Resolution | 1280 X 800 | |
| Light Source | 625nm red LED | |
| Angel | Horizon 42°;Vertical 31° | |
| | 1D | 2D |
| Barcodes | UPC-A/UPC-E EAN13/EAN8/ISBN/ISSN Code128/GS-128 Code39, Code93, Code32, Code11 Codabar, MSI PLSEYY ITF25, STD25 Matrix25, IND25, HK25 Pharma code Telepen Trioptic code Brazilian bank code Postal Code GS1 Databar GS1 Compsite code | QR Code/Mirco QR Data Martrix PDF417/Mirco pdf417 Aztec Maxicode Hanxin |
| Precision: | 1D:5mil Code 39 | 2D:6.5mil QR code |
| Print Contrast: | 25% | |
| Operating temperature: | -20°C~+50°C | |
| Storage temperature: | -40°C~+70°C | |
| Humidity: | 5%~95% (No condensation) | |
| Ambient illumination: | 0~100000LUX | |
| Working Voltage: | DC+5V±5% | |
| Start-up current: | 330mA | |
| Stand-by current: | 190mA | |
| Working current: | 240mA | |
| Interface: | USB COM/Keyboard (RS232 option) | |
| Size: | 144mm*135mm*103mm | |

