

I6 CCD wireless barcode scanner



Features

1. Long communication distance Open outdoor maximum working distance 50-100m
2. Full quakeproof, waterproof, dustproof, antiknock design
3. IP68 Industrial Grade, drop lots of time from 7 high meters still work normally, work under water for more than 30 minutes
4. Solve frequent charging problems; battery lasts 6-10 hours after full charged; base functions as receiver and charger.
5. **Wireless charge** . 2000MAH large capacity battery .
6. **The device has a wireless charging function, the scanner can just charge on the base** .

Optional:

Applicable scope

- ✓ 1.Comercial POS system(Supermarkets)
- ✓ Warehousing and logistics
- ✓ Libraries
- ✓ Banks and Telecom
- ✓ Transportaion
- ✓ Postal service
- ✓ Industrial and manufacturing management

Feature	
Light Resource	C C D (Safe visible light)
Port/Interface	USB (standard), RS232 (optional)
Supported Symbolgies	EAN-8, EAN-13, Codabar, CODE11 , CODE 39, CODE 93, CODE128, China Post, GS1-128, GS1 Limited, GS1 Omnidirectional, UPC-A, UPC-E, ISBN/ISSN, ISBT , Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5 , MSI, Plessey, ITF14
Precision	≥4 mil/0.127mm@PCS90%
Depth of scan field	Code 39:110mm-170mm(0.127mm 5mil) Code 39:100mm-450mm(0.5mm 20mil) Code 39:240mm-480mm(1.0mm 40mil) UPC/EAN 13:100mm-250mm(0.33mm 13mil)
Battery capacity	2000MAH
Resolution	2500
Charging time	7~9 hours
Decode speed	300 times/ second
Decode Error Rate	less than 1/8 million
Print Contrast Signal	≥10°
Scan Angle	Yaw(Skew) 60° Pitch 60°
Safety	Full quakeproof, waterproof, dustproof, antiknock-design and EMI Shielding
Mechanical/ Electrical	
Working Voltage	DC 3.3V ±5%
Current	Maximum current :365mA
Environmetal	
Operating temperature	0°C~+50°C
Storage temperature	20°C~70°C
Humidity	5%-95%
Certifications	CE, IP68, ROHS, FCC

Packing list	
scanner × 1	
User's guide × 1	
Base(Optional) × 1	
cable × 1	

Packing details		
scanner	Size(L*W*H)	170mm*100mm*65mm
	Weight	235g;
	Without Stand	With Stand
Inner Box	1pc/box; 190mm × 115mm ×85mm; 320g	1pc/box; 210mm × 130mm ×100mm; 520g
Carton	50 sets/ctn;33kg/ctn; 600mm×450mm×420 mm	50 sets/ctn; 33kg/ctn; 880mm×450mm×420mm
	70 sets/ctn; 33kg/ctn; 880mm×450mm×420mm	
20FT Container	10500pcs; 150ctns	11250pcs; 225ctns
	7500pcs; 150ctns	
40FT Container	23800pcs; 325ctns	25000pcs; 500ctns
	16250pcs; 325ctns	

Certifications			
			IP68