

## NT-S5/L5 2Dbarcodescanner



### Features

1. New design concept, make operation more comfortable.
2. Applying CMOS image technology, easy to scan.
3. Multiple barcode ability, fast to scan 1D/2Dbarcode andPDF417.
4. Best shape design, anti-knock and quake proof.
5. Multiple interface, support USB,RS232 port.

### Optional:

### Applicable scope

- ✓ Commercial POS system(Supermarkets)
- ✓ Warehousing and logistics
- ✓ Banks and Telecom
- ✓ Transporter
- ✓ Postal service
- ✓ Industrial and manufacturing management

### Scanning Performance Characteristics

Light Source	Indicator light: 528 nm LED; light: 630 nm		
Field of View	34°V x 46° H		
Scan Angle	Roll360°, Pitch ±65°, Yaw ±60°		

### Scan Performance

5mil(Code39)	9.0-12.0cm	10mil (PDF417):	5.0-22.5cm
13mil(100%UPC/EAN):	3.0-30.5cm	10mil(Data matrix):	5.2-24.0cm
Static current 20mil(Code 39)	3.0-42.0cm		

### Symbology Decode Capability

1D	UPC/EAN with supplementals, Code39, Code39 FullASCII, TriopticCode39, RSSvariants, UCC/EAN 128, Code128, Code128Fu IIASCII, Code93, Codabar(NW1), Interleaved 2 of 5,Discrete 2
PDF417	PDF417,microPDF417 and composite codes
Postal	U.S. Poste and Planet, U.K., Japan, Australian, and Dutch
2D	Maxi Code, Data Matrix (ECC 200), QR Code
Print Contrast	>25%
Interfaces	RS-232C;USB (Standard, IBM Sure POS, Macintosh)

### ImagingCharacteristics

Image(Pixels)	0.35 Megapixel ,752 pixels (H)x 480 pixels (V)
Graphics Format	Bitmap, Jpeg, Tiff
Image Transfer	USB 1.1:Upto12Megabits/s,RS232:Up to 115 kb baud rate
Image Transfer Time	Typical USB application is 0.2 seconds with a compressed Jpeg of 100 kb

### Physical Characteristics/User Environment

Voltage and Current	5±10%VDC/350 mA
Operating Temperature	0°- 50° C
Storage Temperature	-40°-70°C
Humidity	5%-95%
Drop/Shock	Withstands2000gtoconcrete
Safety performance	ROHS,FCC and CE Certificate

### Packing list

scanner× 1	
User's guide ×1	
cable ×1	

### Packing details

scanner	Size(L*W*H)	170mm*100mm*70mm
	Weight	235g;
	Without Stand	With Stand
Inner Box	1pc/box;190mm×115mm×85mm;320g	1pc/box;210mm×130mm×100mm;520g
Carton	50sets/ctn;33kg/ctn;600mm×450mm×420mm	50sets/ctn;33kg/ctn;880mm×450mm×420mm
	70sets/ctn;33kg/ctn;880mm×450mm×420mm	
20FT Container	10500pcs;150ctns	11250pcs;225ctns
	7500pcs;150ctns	
40FT Container	23800pcs;325ctns	25000pcs;500ctns
	16250pcs;325ctns	

### Certifications



